

MICROOPTO
MOS 5VTTL/24VDC 0,1A
Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 1429-0

Fax: +49 5231 14292083

www.weidmueller.com



To adjust sensitive TTL signals to the typical voltage level of 24 V DC used in industrial automation applications, the MICROOPTO TTL modules are used. For the protection of the electronics, the sensitive TTL signals require electrical isolation from the 24 V world. To control the opto circuit via the 5 V TTL signal, an additional auxiliary voltage is fed in.

General ordering data

Type	MOS 5VTTL/24VDC 0,1A
Order No.	8937920000
Version	MICROOPTO, solid-state relays, 1 NO contact (Bipolar transistor), Rated control voltage: 5 V TTL, Rated switching voltage: 24 VDC $\pm 20\%$, Continuous current: 100 mA, Screw connection
GTIN (EAN)	4032248716159
Qty.	1 pc(s).

MICROOPTO
MOS 5VTTL/24VDC 0,1A

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Technical data
Dimensions and weights

Width	6.1 mm	Width (inches)	0.24 inch
Height	88.1 mm	Height (inches)	3.468 inch
Depth	97.8 mm	Depth (inches)	3.85 inch
Net weight	34.8 g		

Temperatures

Humidity	5 - 93% rel. humidity, Tu = 40°C, no condensation	Operating temperature	-25 °C...60 °C
Storage temperature	-40 °C...60 °C		

Probability of failure

MTTF	1,686 Years
------	-------------

Control side

Rated control voltage	5 V TTL	Nominal control current	< 100 µA
Power rating	< 0.5 mW	Cut-in / dropout voltage	2 V / 1 V DC
Status indicator	Green LED	Protective circuit	Varistor, Reverse polarity protection
Nominal auxiliary voltage	5 V DC ± 5 % / HIGH: max. 9 mA, LOW: max 400 µA		

Load side

Rated switching voltage	24 VDC ±20%	Continuous current	100 mA
Rated switching current	100 mA	Load category	LC A
Switch-on delay	< 1.3 µ	Switch-off delay	< 1 µs
Voltage drop at max. load	< 1 V	Leakage current	< 20 µA
Short-circuit-proof	No	Protective circuit, load side	Free-wheel diode
max. switching frequency (DC control voltage)	100 kHz	Nominal auxiliary voltage	24 V DC ± 20 % / max. 110 mA

Contact data

Contact type	1 NO contact (Bipolar transistor)
--------------	-----------------------------------

General data

Mounting rail	TS 35	UL 94 flammability rating	V-0
---------------	-------	---------------------------	-----

Insulation coordination

Rated voltage	300 V	Pollution severity	2
Surge voltage category	III	Clearance and creepage distances for control side - load side	> 3 mm
Dielectric strength for control side - load side	3 kV _{eff} / 1 min.	Dielectric strength to mounting rail	4 kV _{eff} / 1 min.
Impulse withstand voltage	4 kV (1.2/50 µs)	Protection degree	IP20

MICROOPTO

MOS 5VTTL/24VDC 0,1A

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Technical data

Further details of approvals / standards

Standards	DIN EN 50178, GL 2003-VI-Abs. 9, IEC 62314, UL508	Certificate No. (GERMLLOYD)
Certificate no. (cULus)	E141197	54853-08

Connection data

Wire connection method	Screw connection	Stripping length, rated connection	7 mm
Tightening torque, min.	0.4 Nm	Tightening torque, max.	0.6 Nm
Clamping range, rated connection	2.5 mm ²	Clamping range, rated connection, min.	0.5 mm ²
Clamping range, rated connection, max.	4 mm ²	Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, solid, max.	4 mm ²	Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire connection cross section, finely stranded, max.	2.5 mm ²	Cross-section for connected conductor, finely stranded with wire-end ferrules and plastic collars DIN 46228/4, rated connection, min.	0.5 mm ²
Wire connection cross-section, finely stranded with wire-end ferrules and plastic collars DIN 46228/4, rated connection, max.	1.5 mm ²	Conductor cross-section, flexible, AEH (DIN 46228-1), min.	0.5 mm ²
Conductor cross-section, flexible, AEH (DIN 46228-1), max.	1.5 mm ²	Blade size	0.6 x 3.5 mm

Classifications

ETIM 3.0	EC001504	ETIM 4.0	EC001504
ETIM 5.0	EC001504	ETIM 6.0	EC001504
UNSPSC	30-21-18-01	eClass 5.1	27-27-09-90
eClass 6.2	27-27-09-90	eClass 7.1	27-27-09-90
eClass 8.1	27-27-09-90	eClass 9.0	27-27-09-90
eClass 9.1	27-37-16-04		

Product information

Product information	The cable lengths must not exceed 30 m.
Descriptive text accessories	Accessories and dimensioned drawings: refer to the MICROOPTO Accessories page.

Approvals

Approvals



ROHS Conform

Downloads


Approval/Certificate/Document of Conformity	DE_PA5600_160302_001.pdf
Brochure/Catalogue	CAT 4.2 ELECTR 15/16 EN
Engineering Data	EPLAN, WSCAD
User Documentation	Operating Instructions

MICROOPTO MOS 5VTTL/24VDC 0,1A


Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com

Drawings

Wiring diagram



Dimensional drawing



MICROOPTO MOS 5VTTL/24VDC 0,1A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com

Accessories

ZQV 4N



Spring connection with tension clamp Technology

Tension clamp technology is a universal contact system for all common conductor connection types. Its fantastic level of flexibility makes the tension clamp a profitable alternative connection.

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
ZQV 4N/4 GE	1762620000	Accessories, Cross-connector, 32 A	4032248169771	60 pc(s).
ZQV 4N/3 SW	1794000000	Accessories, Cross-connector, 32 A	4032248233793	60 pc(s).
ZQV 4N/10 GE	1758260000	Accessories, Cross-connector, 32 A	4032248169764	20 pc(s).
ZQV 4N/2 GE	1758250000	Accessories, Cross-connector, 32 A	4032248169795	60 pc(s).
ZQV 4N/20 GE	1909020000	Accessories, Cross-connector, 32 A	4032248535644	20 pc(s).
ZQV 4N/10 SW	1794060000	Accessories, Cross-connector, 32 A	4032248234059	20 pc(s).
ZQV 4N/10 RT	1794040000	Accessories, Cross-connector, 32 A	4032248234004	20 pc(s).
ZQV 4N/4 BL	1794020000	Accessories, Cross-connector, 32 A	4032248233816	60 pc(s).
ZQV 4N/4 SW	1794030000	Accessories, Cross-connector, 32 A	4032248233915	60 pc(s).
ZQV 4N/20 RT	1909150000	Accessories, Cross-connector, 32 A	4032248535934	20 pc(s).
ZQV 4N/20 SW	1909120000	Accessories, Cross-connector, 32 A	4032248535804	20 pc(s).
ZQV 4N/4 RT	1794010000	Accessories, Cross-connector, 32 A	4032248233809	60 pc(s).
ZQV 4N/2 BL	1793960000	Accessories, Cross-connector, 32 A	4032248233755	60 pc(s).
ZQV 4N/2 SW	1793970000	Accessories, Cross-connector, 32 A	4032248233762	60 pc(s).
ZQV 4N/3 BL	1793990000	Accessories, Cross-connector, 32 A	4032248233786	60 pc(s).
ZQV 4N/3 GE	1762630000	Accessories, Cross-connector, 32 A	4032248169788	60 pc(s).
ZQV 4N/3 RT	1793980000	Accessories, Cross-connector, 32 A	4032248233779	60 pc(s).
ZQV 4N/2 RT	1793950000	Accessories, Cross-connector, 32 A	4032248233748	60 pc(s).
ZQV 4N/20 BL	1909100000	Accessories, Cross-connector, 32 A	4032248535774	20 pc(s).

MICROOPTO MOS 5VTTL/24VDC 0,1A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com

Accessories

ZQV 4N/10 [1794050000](#)
BL

Accessories, Cross-
connector, 32 A

4032248234011 20 pc(s).

Slotted screwdriver



VDE insulated screwdriver sets, for working on live parts up to 1000 V AC and 1500 V DC, DIN EN 60900. IEC 900. Each piece is "GS" safety tested. Blade made from fully hardened, high-alloy chromium-vanadium-molybdenum steel, gun-metal finish.

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
SDIS SL	1274660000	Assembly tool, Blade width	4050118072631	1 pc(s).
0.6X3.5X100		(B): 3.5 mm, Blade length: 100 mm, Blade thickness (A): 0.6 mm		

Slotted screwdriver



VDE insulated slot-head screwdriver, SDI DIN 7437, ISO 2380/2, drive output acc. to DIN 5264, ISO 2380/1. SoftFinish grip

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
SDIS	9008390000	Screwdriver, Blade width	4032248056354	1 pc(s).
0.6X3.5X100		(B): 3.5 mm, Blade length: 100 mm, Blade thickness (A): 0.6 mm		

MICROOPTO MOS 5VTTL/24VDC 0,1A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com

Accessories

Tools



Tools for removing the sheathing of uncut power cables and outgoing feeders, plus screwdrivers for installing FieldPower components.

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
SDS	9008330000	Screwdriver, Blade width	4032248056286	1 pc(s).
0.6X3.5X100		(B): 3.5 mm, Blade length: 100 mm, Blade thickness (A): 0.6 mm		

Markers



Extensive range of accessories for the FieldPower® boxes.
Cable seals, plug-in connectors, locking elements and much more.

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
WS 12/6 MC	1609900000	WS, Terminal marker, 12 x	4008190203467	600 pc(s).
NE WS		6 mm, Pitch in mm (P): 6.00 Weidmueller, Allen-Bradley, White		

**MICROOPTO
MOS 5VTTL/24VDC 0,1A****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 1429-0

Fax: +49 5231 14292083

www.weidmueller.com

Accessories**Accessories**

The MICROOPTO range of products provide the user with the tried and tested characteristics of terminal blocks. Pluggable cross-connections and harmonised marking solutions packaged in a minimum design width. Best performance within a small footprint.

- 6.1 mm width
- Plug-in standard ZQV 4N cross-connection
- Suitable for labelling with the MultiCard system
- Suitable for mounting on TS35 rail
- Housing material made of WEMID (higher thermal stability in comparison with polyamide)

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
MOS FEED THROUGH	8973450000	MICROOPTO, Feedthrough terminal, Screw connection	4032248799534	1 pc(s).
MOS SUPPLY	8973460000	MICROOPTO, Supply module, Screw connection	4032248799541	1 pc(s).