

# 8R-N



RoHS compliant

## Soft Touch Pushbutton Switches



### Features

The **8R** Soft-Touch Pushbutton switches has a unique snap action structure which provides light and soft tactile feel. The short travel distance (Alternate action: 2.5 mm, Momentary: 1 mm) and the low-profile design make the 8R series suitable for applications where panel space is limited.


### Specifications

Rating	Silver plated	3A 125VAC (Resistive load)	
	Gold plated	Max. 60mA 30VDC (Resistive load)	
Initial contact resistance	Silver plated	10mΩ max. (1A 2~4VDC)	
	Gold plated	20mΩ max. (5mA 200μVAC)	
Initial Dielectric strength	1,000VAC 1 minute		
Initial insulation resistance	1,000MΩ min. (500VDC)		
Electrical life	25,000 operations (50,000 operations:Gold plate)		
Operating temperature range	-20°C~+85°C		
Storage temperature range	-40°C~+85°C		
Operating force	Alternate type	8R101-N-Z	3.92±1.96N
		8R201-N-Z	4.9± <sup>2.94</sup> <sub>1.96</sub> N
	Momentary type	8R102-N-Z	2.94±0.98N
		8R202-N-Z	4.9± <sup>1.96</sup> <sub>0.98</sub> N

### Table of Part Numbers

Terminal style		1-pole	2-pole
Solder	ON - ON	8R1011-N-Z ★8R1011B-N-Z	★8R2011-N-Z ★8R2011B-N-Z
	ON -(ON)	8R1021-N-Z 8R1021B-N-Z	8R2021-N-Z ★8R2021B-N-Z
PC	ON - ON	☆8R1012-N-Z ☆8R1012B-N-Z	★8R2012-N-Z ★8R2012B-N-Z
	ON -(ON)	8R1022-N-Z ☆8R1022B-N-Z	8R2022-N-Z ★8R2022B-N-Z


### PC Hole Layouts




### Terminal Styles ..... Page 263.

### Panel Cut-Out Dimensions

Panel thickness : 2 mm max.



With Locking Ring




Without Locking Ring

SPDT



Terminal numbers are not shown on the switch.




Switching function		
Part No.		
※ 8R101■-N-Z	ON	ON
8R102■-N-Z	ON	(ON)
Connecting terminals	3-2	3-1

■ : Please refer to "Table of Part Numbers" on P.271 for a list of full part numbers.

DPDT



Terminal numbers are not shown on the switch.



Switching function		
Part No.		
※ 8R201■-N-Z	ON	ON
8R202■-N-Z	ON	(ON)
Connecting terminals	3-2 6-5	3-1 6-4


■ : Please refer to "Table of Part Numbers" on P.271 for a list of full part numbers.

Standard Accessories (8R & 8R)

《Supplied with switch》


Hex Nut	Lockwasher	Locking Ring
140008010241	140008030051	140008020062
Nickel plated	Zinc plated	Zinc plated

Color Button Mounting



Snap in the color button on to the actuator.

Part name	Color Button			
Dimension A	φ 8	φ 10	φ 15	
Dimension B	7.5	8	10	
	White	140000481420	140000480082	140000480088
	Red	140000481421	140000480083	140000480089
	Black	140000481422	140000480081	140000480090
	Gray	140000481423	140000480084	140000480091
	Green	140000481424	140000480085	140000480092
	Blue	140000481425	140000480086	140000480093
	Orange	140000481426	140000480087	140000480094
	Yellow	140000481427	140000480371	140000480372



Terminal Style	Number of poles	Switching Function	Parts No.	Dimension A	Dimension B	Dimension C
S/D	1 pole	ON - ON	8R1011■-N-Z	16.5	12.5	2.5
		ON - (ON)	8R1021■-N-Z	15.0	11.0	1.0
	2 poles	ON - ON	8R2011■-N-Z	16.5	12.5	2.5
		ON - (ON)	8R2021■-N-Z	15.0	11.0	1.0
P/C	1 pole	ON - ON	8R1012■-N-Z	18.9	12.5	2.5
		ON - (ON)	8R1022■-N-Z	17.4	11.0	1.0
	2 poles	ON - ON	8R2012■-N-Z	18.9	12.5	2.5
		ON - (ON)	8R2022■-N-Z	17.4	11.0	1.0

■ : Blank for silver-plated contacts. "B" for gold-plated contacts. □ : Gold plated

●Hex Nut (2 pcs), Lockwasher (1 pc), and Locking Ring (1 pc) are supplied with the switch. A Color Button is also supplied with the switch. Please specify the part number from the above table when ordering.

(ON) : Momentary.