




## DIP & SIP SWITCHES



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

### LOW PRO DIP SW 8POS W/TAPE AU

Alcoswitch | 7000

9-435626-2

TE Internal Number: 9-435626-2

Always EU RoHS/ELV Compliant

Product Type **Switch**

Contact Mating Area Plating Material **Gold**

Housing Color **Black**

Housing Material **Glass-Filled Polyester**

Auto-Insertable **No**

#### Product Drawings

[SWITCH ASSY, DIP, TYPE C, 7000 SERIES, SPST, LOW PROFILE](#)

PDF **(TIFF AVAILABLE)**  
English

[SWITCH ASSY, DIP, TYPE C, 7000 SERIES, SPST, LOW PROFILE](#)

PDF **(TIFF AVAILABLE)**  
English

#### CAD Files

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

2D\_DXF.ZIP  
English

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

#### Product Specifications

Product Specification

[Switch, DIP, Premium 7000 Series](#)

PDF  
English

Application Specification

[Dual In-Line Package \(DIP\) Programming Switches \(7000 And 7100 Series\)](#)

PDF  
English

#### Product Environmental Compliance

TE Material Declaration

[MD\\_9-435626-2\\_12302013236\\_dmtec](#)

PDF  
English

#### Instruction Sheets

Instruction Sheet (U.S.)

[Dual In-Line Package \(DIP\) Programming Switches \(7000 And 7100 Series\)](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	<b>Switch</b>
	Sealed	<b>Yes</b>
	Switch Type	<b>DIP</b>
	Actuator Style	<b>Recessed Rocker</b>
Configuration Features	Number of Switches	<b>8</b>
	Configuration (Pole-Throw)	<b>Single Pole - Single Throw</b>
	Number of Positions	<b>8</b>
Electrical Characteristics	Voltage Rating (VDC)	<b>50</b>
Body Features	Seal Type	<b>Tape</b>
Contact Features	Contact Mating Area Plating Material	<b>Gold</b>
	Auto-Insertable	<b>No</b>
	Contact Current Rating (A)	<b>1.5</b>
	Contact Base Material	<b>Gold</b>
	Solder Tail Contact Plating	<b>Gold over Nickel</b>
Termination Features	Termination Post Length	<b>3.56 mm [ .135 in ]</b>
Mechanical Attachment	Mounting Type	<b>Through Hole</b>
	Mounting Angle	<b>Vertical</b>
Housing Features	Housing Color	<b>Black</b>
	Housing Material	<b>Glass-Filled Polyester</b>
	Centerline	<b>2.54 mm [ .1 in ]</b>
	Low Profile	<b>Yes</b>
Dimensions	Height	<b>7.36 mm [ .29 in ]</b>
	Length	<b>22.35 mm [ .88 in ]</b>

Usage Conditions	Operating Temperature Range (°C)	<b>-55 – 105</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
Packaging Features	Packaging Method	<b>Tube, Tube/Box</b>
	Packaging Quantity	<b>14</b>
Other	Comment	<b>Red Band "Off" Position \ Red Band "On" Position, White Rockers and Characters., White dot identifies pin 1.</b>

Product Compliance [Statement of Compliance PDF](#)  
[VIEW ALL PRODUCT COMPLIANCE](#)

## CUSTOMERS ALSO BOUGHT

PCB D-SUB CONNECTORS	M.2 CONNECTORS	STANDARD CIRCULAR I/O CONNECTORS	SURFACE MOUNT RESISTORS
 <p>9w D plg W B/L &amp; 4-40 s/lock 15u" gold 3-1634218-2</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	 <p>M.2 0.5PITCH 3.2H KEY B 15U" AU 2199119-3</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	 <p>M12.MALE.B CODE.5P.PG7.(AU) 4-2271112-1</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	 <p>SMW2 8R2 5% SMW28R2JT</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>