



Main

Range of product	Square D Pumptrol
Product or component type	Mechanical alternator
Device application	Top mounted closed tank
Device short name	9038D
Product specific application	Liquid level control
Electrical circuit type	Power circuit
Quantity per set	Set of 1
Type of packing	Individual

Complementary

Product destination	For open tank or sump
Device mounting	Flange
Cable entry number	8 knock-outs for 1/2" or 3/4" conduit UL 508
Contacts type and composition	4 NC snap action DPST-DB Form YY
Controlled fluid	Corrosive fluid @ specific gravity of 0.85 in or higher 220 °F Hydraulic oil @ specific gravity of 0.85 in or higher 220 °F Sea water @ specific gravity of 0.85 in or higher 220 °F Fresh water @ specific gravity of 0.85 in or higher 220 °F
Motor power kW	0.37 kW 0.5 hp @ 230 V DC 0.37 kW 0.5 hp @ 115 V DC 0.18 kW 0.25 hp @ 32 V DC 0.75 kW 1 hp @ 475 V AC 3 phases 0.75 kW 1 hp @ 460 V AC 3 phases 3.7 kW 5 hp @ 230 V AC 3 phases 2.2 kW 3 hp @ 230 V AC 1 phase 2.2 kW 3 hp @ 115 V AC 3 phases 1.5 kW 2 hp @ 115 V AC 1 phase
Electrical connection	Screw-clamp terminals 10 AWG
Contact operation	Contacts close on liquid rise
Float movement	Variable fixed
Float position	Any
Float rod angle	Horizontal
Short circuit protection	20 A cartridge fuse gG
Local signalling	Without
Materials in contact with fluid	316 stainless steel Nitrile (Buna-N) or equivalent rubber Yellow brass 304 stainless steel
Enclosure material	Painted cold-rolled steel
Operating position	Vertical position only
Electrical durability	100 cycles @ 60 cyc/mn
Mechanical durability	300 cycles
Terminal block type	8 terminals
Operating rate	60 cyc/mn
[Ui] rated insulation voltage	575 V UL 508
Terminals description ISO n°1	Line-load-load-line
Depth	4.47 in

Width	6.84 in
Factory modification	Without
Kit composition	Float switch Rod and float are to be choosen in accessories

Environment

Standards	CE UL 508
Ambient air temperature for operation	-22...220 °F
Ambient air temperature for storage	-22...220 °F
NEMA degree of protection	NEMA 1 UL 50
Product certifications	UL listed file E12158 CSA file LR25490

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 1150 - Schneider Electric declaration of conformity
Product environmental profile	Available  Download Product Environmental
Product end of life instructions	Available  Download End Of Life Manual