

Fuse plug - ST-SILA250-UK 4 - 0921053

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse plug, Nominal current: 6.3 A, Length: 33.1 mm, Width: 6.1 mm, Height: 26.5 mm, Color: black

The illustration shows the version without LED/light indicator

Key commercial data

Packing unit	1 pc
GTIN	 4 017918 010317
Weight per Piece (excluding packing)	5.96 GRM
Custom tariff number	85363010
Country of origin	Poland

Technical data

General

Note	If the fuse is defective, the downstream circuit is not off load
Color	black
Insulating material	PA
Inflammability class according to UL 94	V2

Dimensions

Width	6.1 mm
Length	33.1 mm
Height NS 35/7,5	26.5 mm

General

Fuse	G / 5 x 20
Insulating material group	CTI 600
Nominal current I_N (lower level)	6.3 A
Nominal voltage U_N	250 V

Fuse plug - ST-SILA250-UK 4 - 0921053

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141149
eCl@ss 7.0	27141149
eCl@ss 8.0	27141149

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002018
ETIM 5.0	EC002018

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

CSA / UL Recognized / cUL Recognized / GOST / ABS / GOST / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

Fuse plug - ST-SILA250-UK 4 - 0921053

Approvals

CSA 	
Nominal current I _N	10 A
Nominal voltage U _N	300 V

UL Recognized 	
Nominal current I _N	6.3 A
Nominal voltage U _N	300 V

cUL Recognized 	
Nominal current I _N	6.3 A
Nominal voltage U _N	300 V

GOST 	
--	--

ABS	
Nominal current I _N	10 A
Nominal voltage U _N	300 V

GOST 	
--	--

cULus Recognized 	
--	--

