



## WIRE-TO-BOARD CONNECTOR CONTACTS



TE CONNECTIVITY (TE)

### POS-LOCK FAH-STECKH

Positive Lock | Positive Lock Connection System

926820-3

TE Internal Number: 926820-3

Always EU RoHS/ELV Compliant

Contact Type **Socket**

Wire/Cable Size (AWG) **20 – 15**

Wire/Cable Size (mm<sup>2</sup>) **.5 – 1.5**

Packaging Method **Strip**

✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

#### Product Drawings

[Positive Lock Flag Steckhulse 63](#)

PDF  
English

#### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

#### Catalog Pages/Data Sheets

[1654742\\_HOUSEHOLD\\_APPLIANCES\\_RAST5](#)

PDF  
English

#### Product Specifications

Application Specification

[Series 250 Positive Lock MK 1 Receptacle Connectors](#)

PDF  
English

#### Product Environmental Compliance

TE Material Declaration

[MD\\_926820-3\\_12122015223\\_dmtec](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	<b>Contact</b>
	Applies To	<b>Wire/Cable</b>
	Receptacle Style	<b>Flag</b>
Body Features	Material	<b>Phosphor Bronze</b>
Contact Features	Contact Type	<b>Socket</b>
	Contact Base Material	<b>Phosphor Bronze</b>
	Contact Plating Material	<b>Tin</b>
Termination Features	Crimp Area Plating Material	<b>Tin</b>
Mechanical Attachment	Mating Area Interface Dimensions	<b>.25 x .032 in, 6.35 x .81 mm</b>
Dimensions	Wire/Cable Size (AWG)	<b>20 – 15</b>
	Wire/Cable Size (mm <sup>2</sup> )	<b>.5 – 1.5</b>
	Insulation Diameter	<b>2.2 – 3.1 mm [ .086 – .122 in ]</b>
	Stock Thickness	<b>.015 in, .38 mm</b>
Packaging Features	Packaging Method	<b>Strip</b>
	Packaging Quantity	<b>2000</b>
Product Compliance	<a href="#">Statement of Compliance</a> PDF <a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	