



## POWER CONTACTS



TE CONNECTIVITY (TE)

### UNIVERSAL M-N-L SOCKET

MATE-N-LOK | [Universal MATE-N-LOK](#)

926895-1

TE Internal Number: 926895-1

[Always EU RoHS/ELV Compliant](#)

Product Type **Contact**

Contact Current Rating (A) **19**

Operating Voltage (VAC) **600**

Operating Voltage (VDC) **600**

Wire/Cable Size (AWG) **24 – 18**

✓ Active

[PRODUCT DRAWING](#)  
English

[3D PDF](#)

#### Product Drawings

[Universal M-N-L Socket 0.2-0.8 SQ.MM Wire Range](#)

PDF  
English

[UNIVERSAL MNL SOCKET 0.2-0.8 Mm2 WIRE RANGE](#)

PDF  
English

#### CAD Files

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

2D\_DXF.ZIP  
English

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

#### Product Type Features

#### Product Type

#### Contact

#### Electrical Characteristics

Contact Current Rating (A)

**19**

Operating Voltage (VAC)

**600**

Operating Voltage (VDC)

**600**

Contact Features	Contact Type	<b>Socket</b>
	Contact Base Material	<b>Brass</b>
	Contact Mating Area Plating Material	<b>Pre-Tin</b>
	Contact Design	<b>Split</b>
Termination Features	Wire/Cable Size (AWG)	<b>24 – 18</b>
	Wire/Cable Size (mm <sup>2</sup> )	<b>.2 – .8</b>
	Termination Type	<b>Crimp</b>
Mechanical Attachment	Contact Retention in Housing	<b>With</b>
	Contact Retention in Housing Type	<b>Locking Lance</b>
Dimensions	Accepts Wire Insulation Diameter Range	<b>1 – 2.5 mm [ .039 – .098 in ]</b>
Operation/Application	Operating Temperature Range	<b>-55 – 125 °C [ -67 – 257 °F ]</b>
	Connector System	<b>Wire-to-Wire</b>
Industry Standards	Glow Wire Rating	<b>Standard Part - Not Glow Wire</b>
	UL File Number	<b>E28476</b>
	Agency/Standard	<b>CSA, UL</b>
	VDE Tested	<b>Yes</b>
	CSA File Number	<b>LR 7189</b>
	UL Rating	<b>Recognized</b>
	CSA Rating	<b>Certified</b>
Packaging Features	Packaging Method	<b>Box</b>
	Packaging Quantity	<b>1000</b>
Other	Wire/Cable Type	<b>Discrete Wire</b>
	Wire Type	<b>Stranded</b>
Product Compliance	<a href="#">Statement of Compliance</a> PDF <a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	

## CUSTOMERS ALSO BOUGHT

<p>POWER CONNECTORS</p>  <p>UNIV.M-N-L.PIN 926896-1</p> <p>Save to List Find Similar Products</p>	<p>RECTANGULAR POWER CONNECTORS</p>  <p>HONHUS UMNL V0 9-P 927231-3</p> <p>Save to List Find Similar Products</p>	<p>RECTANGULAR POWER CONNECTORS</p>  <p>05P UMNL PLUG HSG 350809-1</p> <p>Save to List Find Similar Products</p>	<p>POWER CONNECTORS</p>  <p>UMNL PIN 24-18 PTPBR L/F 350690-1</p> <p>Save to List Find Similar Products</p>
--	--	---	--

Products - 207 Results

[View All](#)

Compare 0/10 

Relation Type ▼

RELATIONSHIP

### Housings

Identifies Housings compatible with a given Contact

[See All Housings](#)

	<p>PRODUCT - HOUSINGS</p> <p>Connectors - Rectangular Power Connectors MATE-N-LOK   Universal MATE-N-LOK</p> <p><b>10P UN-MNL AUFN-GEH - 926309-3</b></p> <p>TE INTERNAL NUMBER: 926309-3</p> <p>✓ Active</p> <p>Always EU RoHS/ELV Compliant</p> <p>Product Type <b>Housing</b></p> <p>Housing Type <b>Receptacle</b></p> <p>Connector System <b>Wire-to-Panel,</b> <b>Wire-to-Wire</b></p> <p>Applies To <b>Panel, Wire/Cable</b></p> <p>Number of Positions <b>10</b></p>
---	--

RELATIONSHIP

### Housings

Identifies Housings compatible with a given Contact

[See All Housings](#)

	<p>PRODUCT - HOUSINGS</p> <p>Connectors - Rectangular Power Connectors MATE-N-LOK   Universal MATE-N-LOK</p> <p><b>04P UMNL PLUG HSG NATL - 1-480702-0</b></p> <p>TE INTERNAL NUMBER: 1-480702-0 ALIAS ID: 475838-000, AMPS-1-0480702-0</p> <p>✓ Active</p> <p>Always EU RoHS/ELV Compliant</p> <p>Product Type <b>Housing</b></p> <p>Housing Type <b>Plug</b></p> <p>Connector System <b>Wire-to-Wire</b></p> <p>Applies To <b>Wire/Cable</b></p> <p>Number of Positions <b>4</b></p>
---	--

RELATIONSHIP

### Housings

Identifies Housings compatible with a given Contact

[See All Housings](#)



Connectors - Rectangular Power Connectors  
MATE-N-LOK | Universal MATE-N-LOK

## 04P UMNL CAP HSG GRN - 1-480703-5

TE INTERNAL NUMBER: 1-480703-5

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Receptacle**

Connector System **Wire-to-Panel,**  
**Wire-to-Wire**

Applies To **Panel, Wire/Cable**

Number of Positions **4**