




Connectors for control signals



NR-series

HiPower

Product description

Multi-pole shielded circular connectors. Design according to DIN 43651, all-metal construction, used for control and measurement systems.

- Connection of shielded cables with PG-cable gland, efficient shielding ensures transmission free of electromagnetic and parasitic interference from the PG-cable gland to the machine

- For situations susceptible to interference and safety-related applications
- Suitable for use under extreme mechanical stress

Basic data

Number of poles: 6 + PE, 11 + PE
Operating voltage: 25 V AC; 50 V DC
Operating current:
10 A (6-pole), 5 A (11-pole)

Contact material/surface:

CuZn silver-plated

Protection class: IP 65





Type of connection: crimp / solder

Connection cross-section: max.

1,5 mm² (6-pole), 0,5 mm² (11-pole)

Ambient temperature: -25 ... +90°C

Contacts are to be ordered separately, see chapter: Contacts, crimping systems, accessories





Type		Number of poles	Description	Suitable for	Order no.
 N6R EFS		6 + PE	Cable socket, straight Type of connection: crimp Contacts: RBC 162	N6R BM FA S (EMV-PG-cable gland is to be ordered separately!)	933 711-001
 N6R BM FAS		6 + PE	Surface-mounted connector with flange Type of connection: solder	N6R EF S	933 710-001
 N11R EFS		11 + PE	Cable socket, straight Type of connection: crimp Contacts: RBC 162/1	N11R BM FAS (EMV-PG-cable gland is to be ordered separately!)	933 700-001
 N11R BM FAS		11 + PE	Surface-mounted connector with flange Type of connection: solder	N11R EF S	933 699-001

Contacts and accessories can be found in chapter: Contacts, crimping systems, accessories



NR-series


HiPower

Type		Number of poles	Description	Suitable for	Order no.
 N6R-40		—	Conductive flat gasket	N6R BM FAS, N11R BM FAS	734 633-001
 N6R-41		—	EMV-PG-cable gland for lead diameter 6 - 12 mm	N6R EF S N11R EF S	734 605-001
 N6R-42		—	EMV-PG-cable gland for lead diameter 12 - 15 mm	N6R EF S, N11R EF S	734 606-001
 SHK 4		—	Protective cover for surface-mounted connector	N6R BM FAS, N11R BM FAS	734 582-001

Contacts and accessories can be found in chapter: Contacts, crimping systems, accessories



Connectors for control signals



NR-series

HiPower

Product description

Multi-pole circular connectors according to DIN 43651.

- Robust design
- Casing out of impact-proof, unbreakable plastic, glass-fibre reinforced
- Splash-proof, protection class IP 65 (DIN 40050)
- Vibration-proof connection due to central screw or screw bushing
- Strain relief due to claw cage in the

PG-cable gland

- Colour of product: grey

Basic data

Number of poles: 6 + PE, 11 + PE

Operating voltage:

250 V AC / DC (6-pole)

60 V AC / DC (11-pole)

Operating current: 10 A (6-pole),

5 A (11-pole)

Contact material/surface:

CuZn silver-plated

Protection class: IP 65

Type of connection:

crimp / screw / solder

Connection cross-section: max.




1,5 mm² (6-pole), 0,5 mm² (11-pole)

Outer cable diameter: 7-9 mm

(6-pole), 8-10 mm (11-pole)

Ambient temperature: -30 ... +90°C

Contacts are to be ordered separately, see chapter: Contacts, crimping systems, accessories

Type		Number of poles	Description	Suitable for	Order no.
 N6R FF		6 + PE 	Cable socket, angled Type of connection: crimp Contacts: RBC 162	N6R AM, N6R AM..., N6R BM..., N6R DM	931 435-106
 N6R FF R		6 + PE 	Cable socket, angled with knurled screw Type of connection: crimp Contacts: RBC 162	N6R AM, N6R AM..., N6R BM..., N6R DM	931 553-106
 N6R FF S11		6 + PE 	Cable socket, angled, transparent cap, for installation of the LED insert Type of connection: screw ²	N6R AM, N6R AM..., N6R BM..., N6R DM	932 194-112

1) In accordance with the repl. docs. issued by the German PTT, No. 64.5060.678.00

2) (Socket clamp connection); LED insert type N6R 3 LED 24 or N6R 3 LED 24DB - order separately

Contacts and accessories can be found in chapter: Contacts, crimping systems, accessories

HiPower

Contacts and accessories can be found in chapter: Contacts, crimping systems, accessories








Connectors for control signals



NR-series

HiPower

Type		Number of poles	Description	Suitable for	Order no.
		6 + PE 	Panel-mounted connector with metal screw-in casing, PG 13,5 Type of connection: crimp Contacts: RSC 162	N6R FF, N6R FFR, N6R EF	931 434-001
		6 + PE 	Panel-mounted connector with contact bearer in the casing (monoblock design), PG 13,5 Type of connection: crimp Contacts: RSC 162	N6R FF, N6R FFR, N6R EF	931 592-001
		6 + PE 	Panel-mounted connector with contact bearer in the casing (monoblock design), PG 11 Type of connection: crimp Contacts: RSC 162	N6R FF, N6R FFR, N6R EF N6R EF	931 592-002
		6 + PE 	Panel-mounted connector with contact bearer in the casing (monoblock design), PG 16 Type of connection: crimp Contacts: RSC 162	N6R FF, N6R FFR, N6R EF	931 592-003
		6 + PE 	Panel-mounted connector with metal screw-in insert in the casing (metal segment), PG 13,5 Type of connection: crimp Contacts: RSC 162	N6R FF, N6R FFR, N6R EF	931 773-001






Contacts and accessories can be found in chapter: Contacts, crimping systems, accessories

Connectors for control signals

NR-series

HiPower




Type		Number of poles	Description	Suitable for	Order no.
 N6R AM 2 D		6 + PE 	Panel-mounted connector with contact bearer in the casing (monoblock design), PG 13,5 pins hermetically mounted to prevent ingress of liquids Type of connection: solder	N6R FF, N6R FFR, N6R EF	932 207-206
 N6R BME		6 + PE 	Panel-mounted connector with flange Type of connection: crimp Contacts: RSC 162	N6R FF, N6R FFR, N6R EF	931 731-106
 N6R BM FA		6 + PE 	Surface-mounted connector with flange Type of connection: crimp Contacts: RSC 162	N6R FF, N6R FFR, N6R EF, N6R FF S 11	932 437-206
 N6R AF		6 + PE 	Panel-mounted socket with metal screw-in casing, PG 13,5 Type of connection: crimp Contacts: RBC 162	N6R FMR, N6R EM, N6R DM	931 855-001
 N6R AF 5		6 + PE 	Panel-mounted socket with metal screw-in insert in the casing (metal segment), PG 13,5 Type of connection: crimp Contacts: RBC 162	N6R FMR, N6R EM, N6R DM	932 164-001

Contacts and accessories can be found in chapter: Contacts, crimping systems, accessories









Connectors for control signals



NR-series

HiPower

Type		Number of poles	Description	Suitable for	Order no.
 N6R BFE		6 + PE 	Panel-mounted socket with flange Type of connection: crimp Contacts: RBC 162	N6R FMR, N6R EM, N6R DM	931 730-106
 N6R DM		6 + PE	Coupling connector for cable socket N6R EF Type of connection: crimp Contacts: RSC 162	N6R EF	932 273-106
 N11R FF		11 + PE	Cable socket, angled Type of connection: crimp Contacts: RBC 162/1	N11R AM, N11R AM 5, N11R BM FA	932 632-106
 N11R FM		11 + PE	Cable connector, angled Type of connection: crimp Contacts: RSC 162/1	N11R AF, N11R AF 5	932 633-106
 N11R DM		11 + PE	Coupling connector for cable socket N11R EF Type of connection: crimp Contacts: RSC 162/1	N11R EF	932 629-106






Contacts and accessories can be found in chapter: Contacts, crimping systems, accessories

Connectors for control signals



NR-series


HiPower

Type		Number of poles	Description	Suitable for	Order no.
 N11R BM FA		11 + PE	Surface-mounted connector with flange Type of connection: crimp Contacts: RSC 162/1	N11R FF, N11R EF	932 628-206
 N11R EF		11 + PE	Cable socket, straight Type of connection: crimp Contacts: RBC 162/1	N11R AM, N11R AM 5, N11R BM FA, N11R DM	932 630-106
 N11R EM		11 + PE	Cable connector, straight Type of connection: crimp Contacts: RSC 162/1	N11R AF, N11R AF 5	932 631-106
 N11R AM		11 + PE	Panel-mounted connector with metal screw-in casing, PG 13,5 Type of connection: crimp Contacts: RSC 162/1	N11R FF, N11R EF	932 626-106
 N11R AM 5		11 + PE	Panel-mounted connector with metal screw-in insert in the casing (metal segment), PG 13,5 Type of connection: crimp Contacts: RSC 162/1	N11R FF, N11R EF	932 627-106

Contacts and accessories can be found in chapter: Contacts, crimping systems, accessories







Connectors for control signals



NR-series

HiPower



Type		Number of poles	Description	Suitable for	Order no.
 N11R AF		11 + PE	Panel-mounted socket with metal screw-in casing, PG 13,5 Type of connection: crimp Contacts: RBC 162/1	N11R FM, N11R EM	932 624-106
 N11R AF 5		11 + PE	Panel-mounted socket with metal screw-in insert in the casing (metal segment), PG 13,5 Type of connection: crimp Contacts: RBC 162/1	N11R FM, N11R EM	932 625-106
 NC 6		–	Coding, complete	All connectors N6R...	831 002-011
 N6R-13		–	Central screw with knurled head	Cable connectors and sockets N6R...	731 735-001
 SHK1		–	Protective cover for transport	N6R AM 2, N6R AM 3, N6R AM 4, N6R AM 2 D	733 849-011

Contacts and accessories can be found in chapter: Contacts, crimping systems, accessories



NR-series

HiPower

Type		Number of poles	Description	Order no.
 SHK2		–	Protective cover for transport Suitable for: N6R AM, N6R AM 5, N6R BM FA, N6R AF, N6R AF 5, N6R DM, N11R DM, N11R BM FA, N11R AM, N11R AM 5, N11R AF, N11R AF 5	733 845-001
 SHK4		–	Protective cover for surface-mounted connectors. Suitable for: N6R AM, N6R AM 2, N6R AM 3, N6R AM 4, N6R AM 5, N6R AM 2 D, N6R BME, N6R DM, N6R BM FA, N11R DM, N11R BM FA, N11R AM, N11R AM 5	734 582-001

Contacts and accessories can be found in chapter: Contacts, crimping systems, accessories

Notes



Connectors for control signals

CM-series

HiPower

Product description

Robust, universal circular connector for control lead connections in hydraulic- and pneumatic systems and in special machinery engineering.





- Compatible with connectors according to MIL-C 5015 resp. VG 95 342

- Housing made of impact-resistant plastic, glass-fibre-reinforced, with screw locking systems for trouble-free, permanent connections

- Easy handling for a quick assembly with integrated strain relief

Basic data

Operating voltage: 50 V AC / DC
 Operating current: max. 16 A
 Protection class: IP 67
 Pollution severity class: 3
 Outer cable diameter: 8mm - 14mm
 Contact surface: Cu Zn/Ag
 Type of connection: solder

Type		Number of poles	Description	Order no.
 CM 06 EA 14S-7 S		3	Cable socket, straight design, strain relief by means of a clamp Operating current: 10 A	933 049-100
 CM 06 EA 14S-2 S		4	Cable socket, straight design, strain relief by means of a clamp Operating current: 10 A	932 457-100
 CM 06 EA 14S-5 S		5	Cable socket, straight design, strain relief by means of a clamp Operating current: 10 A	932 841-100
 CM 06 EA 14S-6 S		6	Cable socket, straight design, strain relief by means of a clamp Operating current: 10 A	932 458-100