

datasheet for Koffer-Service Set Elektronik

article number: 932791001



product description:	order number: 932 791-001
scope of delivery:	1x PRUEF 2610 FT 972 318-100 black 1x PRUEF 2610 FT 972 318-101 red 1x MICRO-PRUEF MPS 2 0,64 FT 973 995-100 black 1x MICRO-PRUEF MPS 2 0,64 FT 973 995-101 red 1x MICRO-KLEPS 973 972-100 black 1x MICRO-KLEPS 973 972-101 red 1x KLEPS 064 PCH 974 201-100 black 1x KLEPS 064 PCH 974 201-101 red 1x KLEPS 064 PCH 974 201-102 blue 1x KLEPS 064 PCH 974 201-103 yellow 1x KLEPS 064 PCH 974 201-104 green 1x KLEPS 064 PCH 974 201-106 gray 1x KLEPS 064 PCH 974 201-107 white 1x MZS 4 973 599-100 black 1x MZS 4 973 599-101 red 1x MICRO-SMD CLIP 1 972 416-100 1x MA 260 SH 973 889-100 black 1x MA 260 SH 973 889-101 red 1x AK 2 B 2540 I 972 405-188 yellow/green 1x MLS WS 50/2,5 934 087-100 black 1x MLS WS 50/2,5 934 087-101 red 1x MLS WS 50/2,5 934 087-188 yellow/green 1x MAL N 4-0,64/100-0,25 934 160-100 black 1x MAL N 4-0,64/100-0,25 934 160-101 red 1x MKL 0,64/25-0,25 973 604-100 black 1x MKL 0,64/25-0,25 973 604-101 red 1x BNC AL 0,64 933 844-001 black 1x TKO 5 - PMS 221A 974 312-000 1x 2-Fuß-Positionierer für Oszilloskop Tastköpfe 974 401-000

description:	Service Case electronic, For all tasks of development, service, education and more. Contents: - PRUEF 2610 FT; safety-test probe, shatter-proof insulated sleeve with slender, spring-loaded stainless steel tip and 4mm safety socket - MICRO-PRUEF MPS 2 0.64 FT; miniature test probe with slender, spring-loaded stainless steel tip, for sampling of SMD components with protected 0,64mm connecting plug - MICRO-KLEPS; miniature test clips with 0,64mm connecting plugs and rotating gripper (SMD technology) - KLEPS 064 PCH; miniature test clips with 0,64mm connecting plug for tapping from pins and wires up to Ø 1mm - MZS 4; overmolded plug adapter from 4mm plug on 2mm socket - MICRO-SMD CLIP 1; two-pole test clip for SMD components with flat gripper, one notch for gripping thin wires, electrically insulated Spring and 0,64mm connecting sockets - MA 260 SH; touch-proof miniature alligator clip with 4mm connecting socket, clamping distance: fine wires up to Ø 6mm - AK 2 B 2540 I; wide-opening, contact protected alligator clip, for bolt diameter up to 30mm - MLS WS 50/2.5; safety-test lead, both sides with Ø 4mm stackable safety plugs - MAL N 4-0.64/100-0.25; overmolded test lead (wire 0,25mm²), 4mm spring-loaded plug with onward connection capability and 0,64mm insulated connecting socket - MKL 0.64/25-0.25; test lead (wire 0,25mm²), on both sides 0,64mm insulated connecting sockets - BNC AL 0.64; BNC adapter cable with two insulated 0.64 mm connecting sockets for measuring with oscilloscopes, PC cards, ... - TKO 5 - PMS 221A; high-impedance passive divider probe with bandwidth 150 MHz at division factor 10:1, switchable (20 MHz at a 1:1 split) - 2-footer-positioner for oscilloscope test probes TKO (974 401-000)
typ:	Elektronik
system:	Service Case
order number:	932 791-001