

datasheet for PMS SKS safety
article number: 932795001



product description:	order number: 932 795-001
description:	Test equipment, contents: 1 x measuring line MLS WS 50/1 black (934 068-100), 1 x measuring line MLS WS 50/1 red (934 068-101), 2 x measuring line MLS WS 100/1 black (934 095-100), 2 x measuring line MLS WS 100/1 red (934 095-101), 1 x measuring line MLS WS 200/1 black (934 069-100), 1 x measuring line MLS WS 200/1 red (934 069-101), 1 x clamp-test tip KLEPS 2600 black (972 306-100), 1 x clamp-test tip KLEPS 2600 red (972 306-101), 1 x alligator clip AK 2 B black (932 435-100), 1 x alligator clip AK 2 B red (932 435-101), 1 x test tip PRUEF 2600 black (972 317-100), 1 x test tip PRUEF 2600 red (972 317-101)
typ:	PMS SKS safety
system:	4mm safety system
order number:	932 795-001
clamping range:	4mm - 9,5mm
technical data	
measurement category	CAT II // PRUEF 2600, KLEPS 2600: CAT III
norm	DIN EN 61010-031
type of contact:	pin (spring-loaded), socket (unsprung), clamp
type of termination:	4mm pin // socket
cable type:	LEH-XY
cable specification:	highly flexible lead
wire stranding:	259 x 0,07
rated voltage:	AC/DC 1000 V // AK 2 B: 300 V
cable length:	50cm, 100cm, 200cm
conductor size:	1mm ²
cable material:	PVC
cable color:	each article in black and red.
environmental conditions:	
temperature range:	-15 °C to +70 °C