

Anaerobic Connector, ST[®] Compatible

50 µm multimode (OM3/OM4/OM4 extended 10G distance)

CORNING

Corning anaerobic-cured connectors offer optical performance in a fast, easy field-termination solution designed for fiber-to-the-workstation applications for single-mode and multimode connections. This connector combines the quick-cured convenience of anaerobic adhesive with the performance of epoxy-and-polish connectors. Ideal for enterprise networks and any installations requiring field-installed connectors, the anaerobic-cured technology enables fiber optic networks to be installed cost effectively with minimal tools. Installation of the connector can be accomplished in minutes with the anaerobic adhesive two-part epoxy process. The adhesive is first injected into the connector ferrule, and then the fiber is dipped into the primer and inserted into the connector. Curing takes only one minute without the use of lamps or ovens. With the hand-polish process, an average insertion loss of 0.2 dB is achieved.

Features and Benefits

Quick-cure epoxy

No lamps or ovens needed

Minimal tools and no index-matching gel

Low installation cost

Hand polished for minimum insertion loss

Reliability and optical performance

Standards

Intermateability

Compliant with TIA/EIA
604-2



Part Number: 95-051-52-SP-X



Part Number: 95-051-52-SP-X

Anaerobic Connector, ST[®] Compatible

50 µm multimode (OM3/OM4/OM4 extended 10G distance)

CORNING

Specifications

General Specifications

Technology	Field Polish (anaerobic)
Keyed	No
Packaging	Single Pack
Product Type	Field-Installable Connectors
Corning Logo	Yes
Fiber Category	50 µm MM (OM3/OM4/OM4 extended 10G distance)

Design - Connector

Connector Type	ST [®] Compatible
Ferrule	Ceramic
Housing Material	Metal
Housing Color	Metal
Boot Color	Aqua

Mechanical Specifications - Connector

Temperature Cycling	≤ 0.3 dB IL, -40° to +75°C, 21 cycles
---------------------	---------------------------------------

Optical Specifications - Connector

Insertion Loss, Typical	≤ 0.2 dB
Insertion Loss, Maximum	≤ 0.75 dB
Reflectance	≤ -26 dB

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	-----------------------------------------------------------

Anaerobic Connector, ST[®] Compatible

50 µm multimode (OM3/OM4/OM4 extended 10G distance)



Ordering Information

Part Number	95-051-52-SP-X
Product Description	ST [®] Compatible Connector, 50 µm multimode (OM3/OM4/OM4 extended 10G distance), ceramic ferrule, metal hardware; single pack, metal housing, aqua boot

Shipping Information

Units per Delivery	1/1
Package Contents	Connector, Crimp Band (1.6/2.0 mm), Crimp Band (3.0 mm), Boot (900 µm), Boot (2.0 mm), Boot (3.0 mm)



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. Corning Optical Communications is ISO 9001 certified. © 2014 Corning Optical Communications. All rights reserved.

