

SPI



- Metal band is long wearing, easy to clean, and makes superior contact with more reliable path-to-ground*
- Adjusts quickly and easily to any size
- Chrome plate painted outer surface with durable insulative layer
- Nonallergenic stainless steel will not cause an allergic reaction in most people
- 4mm snap
- Coiling on cord provides for ease of movement
- Coil cord includes one megohm resistor

Item	Description	Min. Band Circumference	Max. Band Circumference
95007	Band Only, Black, XL	7"	8.25"
95011	Band Only, Light Blue	5.875"	7"
95041	95007 Wristband with 6' Coil Cord	7"	8.25"
95023	95007 Wristband with 12' Coil Cord	7"	8.25"

* "Note: Metal expansion bracelet style wrist cuffs may trap moisture underneath and can be more effective for people with dry skin." (ESD Handbook TR20.20 section 5.3.2.4.3)

"All personnel shall be bonded or electrically connected to the grounding / equipotential bonding system when handling ESDS [ESD sensitive] items." "When personnel are seated at ESD protective workstations, they shall be connected to the grounding / equipotential bonding system via a wrist strap system." (ANSI/ESDS20.20-2007 sections 8.1 and 8.2)

WRISTBAND, ADJUSTABLE METAL, 4MM SNAP

ESD SYSTEMS.com

ESD SYSTEMS.COM
432 NORTHBORO ROAD CENTRAL
MARLBORO, MA 01752 USA
TEL. (508) 485-7390 FAX (508) 480-0257



Visit our online
library of Tech Drawings:
ESDSystems.com

DRAWING NUMBER
95007

DATE:
December
2008

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Desco:](#)

[95007](#)