

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0950097441

Status:

Active

Overview:

Magnetic and Modular Jacks and Plugs

Description:

Modular Jack, Right Angle, Through Hole, 4/4, Panel Stops

Documents:

- 3D Model

Test Summary STR-1422-001 (PDF)
- Drawing (PDF)

RoHS Certificate of Compliance (PDF)
- Product Specification PS-95009-001-001 (PDF)

Product Literature (PDF)

Agency Certification

UL

E107635

General

Product Family

Modular Jacks/Plugs

Series

95009

Comments

Flush Mount

Component Type

PCB Jack

Magnetic

No

Overview

Magnetic and Modular Jacks and Plugs

Performance Category

3

Power over Ethernet (PoE)

N/A

Product Literature Order No

987650-8441

Product Name

Modular Jack 4/4

UPC

884982793781

Physical

Color - Resin

Black

Durability (mating cycles max)

2500

Flammability

94V-0

Inverted / Top Latch

No

Jack Height

16.00mm

Lightpipes/LEDs

None

Material - Metal

Copper Alloy

Material - Plating Mating

Gold over Palladium Nickel

Material - Plating Termination

Tin

Material - Resin

High Temperature Thermoplastic

Net Weight

2.485/g

Orientation

Right Angle (Side Entry)

PCB Locator

Yes

PCB Retention

Yes

PCB Thickness - Recommended

1.57mm

Packaging Type

Tray

Panel Mount

With Flange

Pitch - Mating Interface

1.02mm

Pitch - Termination Interface

1.27mm

Plating min - Mating

1.270µm

Plating min - Termination

1.905µm

Ports

1

Positions / Loaded Contacts

4/4

Surface Mount Compatible (SMC)

No

Temperature Range - Operating

-40°C to +80°C

Termination Interface: Style

Through Hole


Waterproof / Dustproof

No

Wire/Cable Type

N/A

Electrical



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

China RoHS

REACH SVHC

Not Contained Per -
ED/30/2017 (7 July
2017)

Halogen-Free

Status

Not Low-Halogen

Need more information on product
environmental compliance?

Email productcompliance@molex.com
Please visit the [Contact Us](#) section for any
non-product compliance questions.

China ROHS

Green Image

ELV

Not Relevant

RoHS Phthalates

Not Contained

Search Parts in this Series

95009 Series

Mates With

FCC 68 Plugs

Current - Maximum per Contact
Shielded
Voltage - Maximum

1.5A
No
125V DC

Material Info

Reference - Drawing Numbers

Product Specification
Sales Drawing
Test Summary

PS-95009-001-001
SDA-95009-F
STR-1422-001

This document was generated on 01/03/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex:

95009-7441