

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** [0955032661](#)  
**Status:** **Active**  
**Overview:** [Magnetic and Modular Jacks and Plugs](#)  
**Description:** Modular Jack, Vertical, Top Entry, Through Hole,6/6, No Key Version, Tray

**Documents:**

|                                                                  |                                                      |
|------------------------------------------------------------------|------------------------------------------------------|
| <a href="#">3D Model</a>                                         | <a href="#">Test Summary STR-1181-001 (PDF)</a>      |
| <a href="#">Drawing (PDF)</a>                                    | <a href="#">Test Summary STR-1429-001 (PDF)</a>      |
| <a href="#">Product Specification PS-95503-001-001 (PDF)</a>     | <a href="#">RoHS Certificate of Compliance (PDF)</a> |
| <a href="#">Application Specification AS-85513-001-001 (PDF)</a> | <a href="#">Product Literature (PDF)</a>             |

**Agency Certification**


UL E107635

**General**

|                             |                                                      |
|-----------------------------|------------------------------------------------------|
| Product Family              | Modular Jacks/Plugs                                  |
| Series                      | <a href="#">95503</a>                                |
| Comments                    | Reflow Capable                                       |
| Component Type              | PCB Jack                                             |
| Magnetic                    | No                                                   |
| Overview                    | <a href="#">Magnetic and Modular Jacks and Plugs</a> |
| Performance Category        | 3                                                    |
| Power over Ethernet (PoE)   | N/A                                                  |
| Product Literature Order No | 987650-8441                                          |
| Product Name                | Modular Jack 6/6                                     |
| UPC                         | 800756804811                                         |

**Physical**

|                                |                                |
|--------------------------------|--------------------------------|
| Boot Color                     | N/A                            |
| Color - Resin                  | Black                          |
| Durability (mating cycles max) | 2500                           |
| Flammability                   | 94V-0                          |
| Inverted / Top Latch           | No                             |
| Jack Height                    | 15.70mm                        |
| Keying to Mating Part          | None                           |
| Lightpipes/LEDs                | None                           |
| Material - Metal               | Copper Alloy                   |
| Material - Plating Mating      | Gold over Palladium Nickel     |
| Material - Plating Termination | Tin                            |
| Material - Resin               | High Temperature Thermoplastic |
| Net Weight                     | 2.491/g                        |
| Orientation                    | Vertical (Top Entry)           |
| PCB Locator                    | Yes                            |
| PCB Retention                  | Yes                            |
| PCB Thickness - Recommended    | 1.57mm                         |
| Packaging Type                 | Tray                           |
| Pitch - Mating Interface       | 1.02mm                         |
| Pitch - Termination Interface  | 1.27mm                         |
| Plating min - Mating           | 0.051µm, 1.016µm               |
| Plating min - Termination      | 1.905µm                        |
| Ports                          | 1                              |
| Positions / Loaded Contacts    | 6/6                            |
| Surface Mount Compatible (SMC) | Yes                            |
| Temperature Range - Operating  | -40°C to +85°C                 |
| Termination Interface: Style   | Through Hole                   |
| Waterproof / Dustproof         | No                             |
| Wire/Cable Type                | N/A                            |



Series image - Reference only

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**China RoHS**

**REACH SVHC**

Not Contained Per -  
ED/30/2017 (7 July  
2017)

**Halogen-Free**

**Status**

**Low-Halogen**

**Need more information on product  
environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
Please visit the [Contact Us](#) section for any  
non-product compliance questions.

|                 |               |
|-----------------|---------------|
| China ROHS      | Green Image   |
| ELV             | Not Relevant  |
| RoHS Phthalates | Not Contained |

**Search Parts in this Series**

[95503](#) Series

**Mates With**

[90075](#) Modular Plug

**Electrical**

|                               |         |
|-------------------------------|---------|
| Current - Maximum per Contact | 1.5A    |
| Shielded                      | No      |
| Voltage - Maximum             | 125V DC |

**Solder Process Data**

|                                                |      |
|------------------------------------------------|------|
| Duration at Max. Process Temperature (seconds) | 005  |
| Lead-freeProcess Capability                    | WAVE |
| Max. Cycles at Max. Process Temperature        | 001  |
| Process Temperature max. C                     | 260  |

**Material Info**

**Reference - Drawing Numbers**

|                           |                            |
|---------------------------|----------------------------|
| Application Specification | AS-85513-001-001           |
| Product Specification     | PS-95503-001-001           |
| Sales Drawing             | SD-95503-003               |
| Test Summary              | STR-1181-001, STR-1429-001 |

This document was generated on 10/11/2017

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[95503-2661](#)