





TERMINAL FINISH: SOLDER	
BUSHING FINISH: SILVER	
CAPACITANCE	5000pF GMV
TEMP. RANGE	-55°C TO 125°C
CURRENT	10 AMP
WORKING VOLTAGE	85°C 150 VDC 125°C 100 VDC
D.C. RESISTANCE	.01ohms MAX.
MIN. I.L. PER MIL-STD-220 AT 25°C NO LOAD	
FREQ. MHz	I.L. (db)
10	15
100	30
1 GHz	50
10 GHz	70

SCHEMATIC



MARKING:

PART: S502P

BAG: SCI 9900-381-6004

DATE CODE

LOT No.

QTY/BAG (200 MAX.)

NOTE: HARDWARE IS INCLUDED.

	7	6	5	4	3	2	1	0	REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED	 ERIE, FAIRVIEW PENNSYLVANIA	
	CN 210924	CN 207901	CN 201133	CN 200398	CN 178311	CN 148903 REDRAWN	CN 148347	CN 146343	CHANGE NOTICE	Fractions ± 1/64		
										Dec. .xx±	Dwn. Humphreys	Description
										Dec. .xxx± .010	Ckd. 7/3/02	F/T FILTER
										Angles ±0° 30'	Engr. Keith W.	9900-381-6004
										CODE IDENT. NO. 0LSP2	Scale NONE	