

HC49/U CRYSTAL

AB

 RoHS/RoHS II Compliant



11.5 x 5.0 x 13.46mm

Moisture Sensitivity Level (MSL) – This product is not Moisture Sensitive - MSL = 1

FEATURES:

- High precision availability
- Resistance welded
- Ideal for large pullability application
- Wide frequency range

APPLICATIONS:

- CPU, Memory
- Computer, printer
- Data communication (1MHz)
- Data input - output machine (1MHz)

STANDARD SPECIFICATIONS:

Parameters	Minimum	Typical	Maximum	Units	Notes
Frequency Range	1.8432		160.000	MHz	
Operation Mode	Fundamental				1.8432MHz – 24.000MHz
	3 rd Overtone				24.01MHz – 66.00MHz
	5 th Overtone				66.01MHz – 122.00MHz
	7 th Overtone				122.01MHz – 160.00MHz
Operating Temperature	0		+70	°C	See options
Storage Temperature	-55		+125	°C	
Frequency Tolerance @+25°C	-50		+50	ppm	See options
Frequency Stability over the operating temperature (ref. to +25°C)	-100		+100	ppm	See options
Equivalent series resistance (R1)	See table 1 below			Ω	
Shunt capacitance (C0)			7	pF	
Load capacitance (CL)		18		pF	See options
Drive Level		100	1000	μW	
Aging@25°C±3°C			±5	ppm	First year
Insulation Resistance	500			M Ω	@100Vdc±15V
Drive level dependency (DLD), minimum 7 points tested: from 1μW to 500μW.	Change in frequency (Maximum - Minimum) over DLD range < ±10ppm; Change in ESR (Maximum - Minimum) over DLD range < 25% of Max ESR value; Maximum ESR over DLD range < Max ESR value.				

Table 1


FREQUENCY (MHz)	Operation Mode	ESR (Ω) max	
1.8432-1.999	HC49/U Fundamental	750	
2.000-2.399		550	
2.400-2.999		350	
3.000-3.699		200	
3.700-4.199		100	
4.200-4.899		70	
4.900-5.999		50	
6.000-7.999		40	
8.000-9.999		35	
10.000-12.499		30	
12.50-50.00		25	
24.00-66.00		HC49/U (3rd OT)	40
66.01-122.00		HC49/U (5th OT)	80
122.01-160.00	HC49/U (7th OT)	120	



OPTIONS AND PART IDENTIFICATION:

(Left blank if standard)

AB - MHz - - - - - - - -



NOTE:
*: Frequency Stability ±100 ppm max at -10 to +60°C only for BT cut.
**: -10 to +60°C only.
***: Quality factor must be accompanied by a k value

Table 2


CODES	TRIMMED L in(mm)
Q45	0.45 (11.43)
Q40	0.40 (10.16)
Q35	0.35 (8.89)
Q30	0.30 (7.62)
Q25	0.25 (6.35)
Q20	0.20 (5.08)
Q15	0.15 (3.81)
Q10	0.10 (2.54)
Q115	0.115 (2.92)

NOTE: Use appropriate code numbers for other trimmed lengths not listed.
(e.g. Q14 for 0.14 inch (3.55 mm))

HC49/U CRYSTAL


AB

 RoHS/RoHS II Compliant



11.5 x 5.0 x 13.46mm

OUTLINE DRAWING:



HC49/U CRYSTAL

AB

Pb | RoHS/RoHS II Compliant




11.5 x 5.0 x 13.46mm

OUTLINE DIMENSION CONTD...

Metal Jacket Formed Leads


For Option MJ



Dimensions: mm

TAPE & REEL:

T: 1,000 pcs/reel



Dimensions: mm

ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

ABRACON IS
ISO 9001:2008
CERTIFIED



Visit www.abracon.com for Terms & Conditions of Sale
30332 Esperanza, Rancho Santa Margarita, California 92688
tel 949-546-8000 | fax 949-546-8001 | www.abracon.com

Revised: 07.09.14

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ABRACON:

[AB-25.000MHZ-B2F](#) [AB-27.000MHZ-B2F](#) [AB-14.4756MHZ-B2](#) [AB-7.3728MHZ-B2](#) [AB-19.6608MHZ-B2](#) [AB-20.000MHZ-B2](#) [AB-4.000MHZ-B2](#) [AB-6.7458MHZ-20D](#) [AB-50.000MHZ-B2](#) [AB-48.000MHZ-B2](#) [AB-1.8432MHZ-B2](#) [AB-11.0592MHZ-B2](#) [AB-14.7456MHZ-B2](#) [AB-5.000MHZ-B2](#) [AB-18.432MHZ-B2](#) [AB-22.1184MHZ-B2](#) [AB-16.000MHZ-B2](#) [AB-24.000MHZ-B2](#) [AB-12.228MHZ-B2](#) [AB-12.288MHZ-B2](#) [AB-14.31818MHZ-B2](#) [AB-24.576MHZ-FB2](#) [AB-2.000MHZ-B2](#) [AB-32.768MHZ-B2](#) [AB-4.9152MHZ-B2](#) [AB-6.000MHZ-B2](#) [AB-9.8304MHZ-B2](#) [AB-10.000MHZ-B2](#) [AB-3.6864MHZ-B2](#) [AB-24.576MHZ-B2F](#) [AB-8.192MHZ-B2](#) [AB-32.000MHZ-B2](#) [AB-8.000MHZ-B2](#) [AB-3.579545MHZ-B2](#) [AB-12.000MHZ-B2](#) [AB-33.000MHZ-4Z-FB](#) [AB-17.734475-B4](#) [AB-20.480MHZ-L](#) [AB-14.7456MHz-1U-V](#) [AB-22.000MHz-1U-V](#) [AB-8.000MHz-1U-V](#)