

Electrical Properties:

Frequency Range: VSWR: Impedance: 50Ω nominal 2.4~2.5/4.9~5.35/5.725~5.85 GHz

2 dBi <2.0:1

Gain: Radiation: Omni

Polarization: Wave:

Half Wave Dipole Vertical

Mechanical Properties:

Connector:

Material:

Whip:

Swivel Mechanism: Connector:

Storage Temp.: Operation Temp.:

-30°C to +75°C

SMA type

Polyurethene(Black)

Brass with black chrome plating Polycarbonate(Black) -20°C to +65°C

This is a RoHS compliant product.

Series Part Numbers

АН	AM	Connector Code -XX-
SMA Plug Reverse Polarity T131AH-2.4/4.9/5.x-S	SMA Plug	Description
T131AH-2.4/4.9/5.x-S	T131AM-2.4/4.9/5.x-S	P/N

Connector Interface



SMA Plug (AM)



SMA Plug Reverse Polarity

SCALE	UNIT		!
	DWG. NO.		Multi-E
	T131XX-2.4/4.9/5.x-S	-131 Model	Multi-Band Swivel Antenna
		04/02/06	Rev. Date
		1 of 1	SHEET

none

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

B&B Electronics:

ACH2-DBAT-DP002