

ACT631SMX-4

Compatible with Eu Directive
 2002/EC - RoHS


The **ACT631SMX-4** is a 4 pad, high quality, low aging, metal seam, packaged crystal suitable for automatic placement on printed circuit boards. It utilises a ceramic base and metal lid for durability. the lid is grounded through the package and the pads are gold plated. With a wide frequency range, and tight stability it has become one of the optimum choices for design engineers. **Applications** include Communications, Microprocessor Systems, Instrumentation and many more.

Specification



Parameter	Symbol	Specification	Condition
Frequency Range	fo	10.00 ~ 120.00 MHz	Please specify
Frequency Tolerance (@25°C)	$\Delta f/f_0$	$\pm 10, \pm 15, \pm 30, \pm 50$ & ± 100 ppm	(± 7.5 ppm available to 24.999MHz)
Stability over Temp Range	Tc	See Table 2	Please specify
Temp Operating Range	Topr	-10~+60°C, -20~+70°C, -40~+85°C	Please specify
Temp Storage Range	Tstg	-40 ~ +85°C	
Equivalent Series Resistance	ESR	See Table 1	
Load Capacitance	CL	8 ~ 50pF or Series	Please specify
Shunt Capacitance	C0	7pF max	
Drive Level	DL	100 μ W Typical	(100 μ W ~ 1.0mW options available)
Insulation Resistance	IR	500M Ω min	@100V DC
Aging	Fa	± 5 ppm / year max	@25°C

Frequency Range (MHz)	ESR (Ω) max	Mode
10.000~11.999	70	Fundamental
12.000~19.999	60	Fundamental
20.000~34.999	50	Fundamental
35.000~43.999	40	Fundamental
44.000~120.000	80	3 rd Overtone



Please note that all parameters can not necessarily be specified in the same device
 Customer to specify : Frequency, Frequency Tolerance, Temperature Stability, Operating Temperature & Load Capacitance
 In line with our ongoing policy of product evolution and improvement, the above specification may be subject to change without notice
 ISO9001:2000 Registered

For quotations or further information please contact us at:
 3 The Business Centre, Molly Millars Lane, Wokingham, Berkshire, RG41 2EY, UK
<http://www.actcrystals.com>


Issue 7SKr
 Date 01/11/2005

ACT631SMX-4

Table 2 Frequency Stability VS Temperature Stability

Stability Temp	+/- 5ppm	+/- 7.5ppm	+/- 10ppm	+/- 15ppm	+/- 20ppm	+/- 30ppm	+/- 50ppm	+/- 100ppm
0~+60°C	+	+	+	+	+	+	+	+
-10~+60°C		+	+	+	+	+	+	+
-10~+70°C		+	+	+	+	+	+	+
-20~+70°C		+	+	+	+	+	+	+
-30~+60°C		+	+	+	+	+	+	+
-30~+70°C			+	+	+	+	+	+
-20~+85°C				+	+	+	+	+
-30~+85°C				+	+	+	+	+
-40~+85°C				+	+	+	+	+
-40~+90°C						+	+	+
-40~+105°C						+	+	+

Maximum Re flow Profile



In line with our ongoing policy of product evolution and improvement, the above specification may be subject to change without notice

ISO9001:2000 Registered

For quotations or further information please contact us at:

3 The Business Centre, Molly Millars Lane, Wokingham, Berkshire, RG41 2EY, UK

<http://www.actcrystals.com>


Issue 7SKr

Date 01/11/2005

ACT631SMX-4

TAPE & REEL SPECIFICATION

(1K per reel)



In line with our ongoing policy of product evolution and improvement, the above specification may be subject to change without notice

ISO9001:2000 Registered

For quotations or further information please contact us at:

3 The Business Centre, Molly Millars Lane, Wokingham, Berkshire, RG41 2EY, UK

<http://www.actcrystals.com>

Issue 7SKr

Date 01/11/2005