




▲ 7 pos.

◆ Features

1. Slim design and smooth contour for connection inside small spaces
2. Secure positive lock with tactile click and visible lock confirmation
3. Protected crimp contact from deformation
4. Contact lance for secure connection
5. Wide pin count variations available from 2 to 7 and 13 pos.
6. RoHS compliant

◆ Optimized design for connection inside small space

[7 pos. in mated condition]




Applicable Cable:

AWG#22 to 30 (Outer dia: ϕ 0.75 to 1.45 mm)

Multi-Row Pin Layout

Contacts are arranged in grid, making the diagonal diameter small.

[3 rows for 7 pos.]



Smooth Contour


Connector outline is designed to be smooth, eliminating being caught in the middle of small space during wiring.

No Metal Exposure

No metal component is exposed, avoiding accidental conduction to metal caliber.

Conventional Single Row Product

1. Too wide to go through small space.
2. With rough outline and lock hock, it could be blocked up inside small spaces.



Specifications herein are subject to change without notice. Contact Hirose for latest specifications, drawings or availabilities.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Hirose Electric:](#)

[AP105-DF62-2428\(61\)](#) [AP105-DF62-2428\(64\)](#) [AP105-DF62-2428](#) [AP105-DF62-2428\(63\)](#) [AP105-DF62-2428\(66\)](#)
[AP105-DF62-2428\(65\)](#) [AP105-DF62-2428\(62\)](#)