


ASMT-CB20

SMT Top Fire ChipLED

Data Sheet



Package Drawing



- All dimensions in millimeters.
- Tolerance is ± 0.1 mm unless otherwise specified.
- Electrode Ag plated.

Device Selection Guide

Part Number	Color	Chip
ASMT-CB20	Blue	InGaN


CAUTION: Class 1B static sensitive device per JESD22A114. Please observe appropriate precautions during handling and processing.

Absolute Maximum Ratings at $T_A = 25^{\circ}\text{C}$


Parameter	Rating	Unit
DC Forward Current	10	mA
Power Dissipation	32	mW
Operating Temperature	-40 to +85	$^{\circ}\text{C}$
Storage Temperature	-40 to +85	$^{\circ}\text{C}$
Moisture Sensitivity Level (IPC/JEDEC JSTD020)	2A	-

Optical-Electrical Characteristics at $T_A = 25^{\circ}\text{C}$


Parameter	Test condition	Rating			Unit
		Min	Typ	Max	
Luminous intensity (I_v)	$I_F=5\text{mA}$	11.2	25.0	71.5	mcd
Viewing Angle ($2\theta_{1/2}$)	$I_F=5\text{mA}$		130		deg.
Peak wavelength (λ_p)	$I_F=5\text{mA}$		468		nm
Dominant wavelength (λ_d)	$I_F=5\text{mA}$	465		475	nm
Forward voltage (V_F)	$I_F=5\text{mA}$	2.55		3.15	V




Relative Luminous Intensity vs. Forward Current




Relative Intensity vs. Wavelength




Radiation Pattern




Forward Current vs. Forward Voltage




Forward Current vs. Ambient Temperature



Recommended Soldering Land Pattern



Recommended Pb-Free Reflow Soldering Profile



AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com