
HS

AT-2600 Series

Specifications herein are subject to change without notice.

Waterproof Fixed Attenuators (N Type)







♦ Features

- 1.It conforms to a waterproof and a dustproof standard of IEC529 and IP65W.(*1engagement)
- 2.A high frequency performance excellent by Hirose Electric original high frequency matching technology is achieved.
- 3. The metal film resistor is used for the attenuation element and the high trust design.

♦ Typical Data





♦ Applications

Mobile Phone Base Stations and Other High Frequency Applications.

♦ Specifications

*1.This product is not intended to be waterproof about the connector opening. When connecting this product with cable or other electric device, be careful so that there is no water based material leakage in the connector. Moreover, be sure that the start point of the processing (taping etc) is roof of the connector regarding the waterproof processing at the mating part of the connector.

Part Number	Frequency (GHz)	V.S.W.R. (MAX)	Attenuation (dB)	Power (W)	Connectors
AT-2606	DC-3	1.3	5.3-6.7	16	N-P·J
AT-2610	DC-3	1.3	9.0-11.0	16	N-P·J

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Hirose Electric:
AT-2606 AT-2610 AT-3303