



SAW Components

SAW Rx 2in1 input duplex filter

GSM1800 / GSM1900

Series/type:	B9514
Ordering code:	B39202B9514P810
Date:	February 01, 2011
Version:	2.0

© EPCOS AG 2015. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

EPCOS AG is a TDK Group Company.

SAW Components

B9514

SAW Rx 2in1 input duplex filter

1842.5 / 1960.0 MHz

Data sheet




Application

- Low-loss 2in1 RF filter for mobile telephone GSM1900 and GSM1800 systems, receive path (Rx)
- Usable passband:
Filter 1 (GSM1800): 75 MHz
Filter 2 (GSM1900): 60 MHz
- Unbalanced to balanced operation for both filters
- Impedance transformation from 50 Ω to 150 Ω for both filters
- Low amplitude ripple
- Suitable for GPRS class 1 to 12




Features

- Package size 1.8 x 1.4 x 0.68 mm³
- RoHS compatible
- Approx. weight 0.006g
- Package for Surface Mount Technology (SMT)
- Ni, gold-plated terminals
- Electrostatic Sensitive Device (ESD)
- Moisture Sensitive Level 3



Pin configuration

- 1 Input [Duplex]
- 8,9 Output balanced [Filter 1]
- 6,7 Output balanced [Filter 2]
- 2,3,4,5,10 Case-ground



SAW Components
B9514
SAW Rx 2in1 input duplex filter
1842.5 / 1960.0 MHz
Data sheet

Characteristics of Filter 1 (GSM1800)



Temperature range for specification: $T = -30\text{ }^{\circ}\text{C to }+85\text{ }^{\circ}\text{C}$
 Terminating source impedance: $Z_S = 50\text{ }\Omega \parallel 3.3\text{nH}$
 Terminating load impedance: $Z_L = 150\text{ }\Omega \parallel 15\text{nH (balanced)}$





		min.	typ. @ 25 °C	max.	
Center frequency	f_c	—	1842.5	—	MHz
Maximum insertion attenuation 1805.0 ... 1880.0 MHz	$\alpha_{\max}$	—	2.1	2.8	dB
Amplitude ripple (p-p) 1805.0 ... 1880.0 MHz	$\Delta\alpha$	—	0.8	1.6	dB
Input VSWR 1805.0 ... 1880.0 MHz		—	1.5	2.2	
Output VSWR 1805.0 ... 1880.0 MHz		—	1.8	2.3	
CMRR ($ S_{21}-S_{31} / S_{21}+S_{31} $) 1805.0 ... 1880.0 MHz		20	23	—	dB
Attenuation	α				
10.0 ... 940.0 MHz		45	55	—	dB
940.0 ... 1705.0 MHz		20	38	—	dB
1705.0 ... 1785.0 MHz		12	17	—	dB
1920.0 ... 1980.0 MHz		17	25	—	dB
1980.0 ... 2030.0 MHz		25	30	—	dB
2030.0 ... 2700.0 MHz		28	34	—	dB
2700.0 ... 6000.0 MHz		30	43	—	dB

Maximum ratings of Filter 1

Operable temperature range	T	−40/+85	°C	
Storage temperature range	T _{stg}	−40/+85	°C	
DC voltage	V _{DC}	5	V	
ESD voltage	V _{ESD}	50 ¹⁾	V	machine model, 1 pulse
Input Power at				
GSM 850, GSM 900	P _{IN}	15	dBm	effective power in the on-state, duty cycle 4:8
GSM 1800, GSM 1900	P _{IN}	15	dBm	
Tx bands				

¹⁾ acc. to JESD22-A115A (machine model), 1 negative & 1 positive pulse.

Transfer function Filter 1 (GSM1800)

Transfer function Filter 1 (GSM1800) - Wideband


Smith charts Filter 1 (GSM1800)
 S_{11} function

 S_{22} function


SAW Components
B9514
SAW Rx 2in1 input duplex filter
1842.5 / 1960.0 MHz
Data sheet

Characteristics of Filter 2 (GSM1900)



Temperature range for specification:	T	=	-30 °C to +85 °C
Terminating source impedance:	Z_S	=	50 Ω 3.3nH
Terminating load impedance:	Z_L	=	150 Ω 18nH (balanced)





		min.	typ. @ 25 °C	max.	
Center frequency	f_C	—	1960.0	—	MHz
Maximum insertion attenuation 1930.0 ... 1990.0 MHz	$\alpha_{\max}$	—	2.1	3.0	dB
Amplitude ripple (p-p) 1930.0 ... 1990.0 MHz	$\Delta\alpha$	—	0.9	1.8	dB
Input VSWR 1930.0 ... 1990.0 MHz		—	1.5	2.1	
Output VSWR 1930.0 ... 1990.0 MHz		—	1.8	2.1	
CMRR ($ S_{21}-S_{31} / S_{21}+S_{31} $) 1930.0 ... 1990.0 MHz		22	28	—	dB
Attenuation	α				
10.0 ... 1510.0 MHz		40	46	—	dB
1510.0 ... 1830.0 MHz		30	34	—	dB
1830.0 ... 1850.0 MHz		23	32	—	dB
1850.0 ... 1890.0 MHz		18	30	—	dB
1890.0 ... 1910.0 MHz		9	14	—	dB
2010.0 ... 2070.0 MHz		4	16	—	dB
2070.0 ... 2400.0 MHz		21	36	—	dB
2400.0 ... 6000.0 MHz		30	38	—	dB

Maximum ratings of Filter 2

Operable temperature range	T	−40/+85	°C	
Storage temperature range	T _{stg}	−40/+85	°C	
DC voltage	V _{DC}	5	V	
ESD voltage	V _{ESD}	50 ¹⁾	V	machine model, 1 pulse
Input Power at				
GSM 850, GSM 900	P _{IN}	15	dBm	effective power in the on-state, duty cycle 4:8
GSM 1800, GSM 1900	P _{IN}	15	dBm	
Tx bands				

¹⁾ acc. to JESD22-A115A (machine model), 1 negative & 1 positive pulse.

Transfer function Filter 2 (GSM1900)

Transfer function Filter 2 (GSM1900) - Wideband




SAW Components	B9514
SAW Rx 2in1 input duplex filter	1842.5 / 1960.0 MHz
Data sheet	SMD

References

Type	B9514
Ordering code	B39202B9514P810
Marking and package	C61157-A7-A152
Packaging	F61074-V8226-Z000
Date codes	L_1126
S-parameters	B9514_LB_NB.s3p, B9514_LB_WB.s3p B9514_UB_NB.s3p, B9514_UB_WB.s3p See file header for port/pin assignment table.
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."
Matching coils	See Inductor pdf-catalog http://www.tdk.co.jp/tefe02/coil.htm#aname1 and Data Library for circuit simulation http://www.tdk.co.jp/etvcl/index.htm

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com.

Published by EPCOS AG
Surface Acoustic Wave Components Division
P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2011. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FormFit, MiniBlue, MiniCell, MKD, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.