



SAW Components

SAW Duplexer for femtocell

Band 13 (3G/LTE)

Series/type:	B7939
Ordering code:	B39781B7939P810
Date:	February 13, 2013
Version:	2.0


© EPCOS AG 2015. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

EPCOS AG is a TDK Group Company.


Datasheet

Application


- Low-loss SAW duplexer for 3G/LTE femtocell systems (Band 13)
- Low insertion attenuation
- Low amplitude ripple
- Usable passband 10 MHz
- High power durability


Features

- Package size 2.5 * 2.0 * 0.68 mm³
- RoHS compatible
- Package for **Surface Mount Technology (SMT)**
- Ni, Au-plated terminals
- **Electrostatic Sensitive Device (ESD)**
- Moisture Sensitivity Level 3
- RX = UPLINK = 777-787 MHz
- TX = DOWNLINK = 746-756 MHz


Pin configuration

- 3 RX input
- 1 TX input
- 6 Antenna
- 2, 4, 5, 7, 8, 9 To be grounded



SAW Components
B7939
SAW Duplexer for femtocell
782 / 751 MHz
Datasheet

Characteristics

Temperature range for specification:	T = -10 °C to +85 °C
Antenna terminating impedance:	Z _{ANT} = 50 Ω 16 nH
RX terminating impedance:	Z _{RX} = 50 Ω
TX terminating impedance:	Z _{TX} = 50 Ω

		B7939			
Characteristics ANT - RX		min.	typ. @ 25 °C	max.	
Center frequency	f _C		782.0		MHz
Maximum insertion attenuation	α _{max}				
777.0 ... 787.0 MHz		-	2.0	2.5	dB
Amplitude ripple (p-p)	Δα				
777.0 ... 787.0 MHz		-	0.6	1.5	dB
Error Vector Magnitude	EVM ¹⁾				
@f _{carrier} 779.5 ... 784.5 MHz		-	1.8	3.0	%
Input VSWR (ANT port)					
777.0 ... 787.0 MHz		-	1.5	1.8	
Output VSWR (RX port)					
777.0 ... 787.0 MHz		-	1.5	1.8	
Attenuation	α				
10.0 ... 150.0 MHz		40	58	-	dB
150.0 ... 350.0 MHz		35	45	-	dB
350.0 ... 650.0 MHz		30	41	-	dB
728.0 ... 746.0 MHz		35	47	-	dB
746.0 ... 756.0 MHz		50	56	-	dB
758.0 ... 768.0 MHz		28	31	-	dB
808.0 ... 818.0 MHz		35	44	-	dB
859.0 ... 894.0 MHz		35	44	-	dB
1452.0 ... 1492.0 MHz		40	48	-	dB
1554.0 ... 1574.0 MHz		40	49	-	dB
1574.0 ... 1606.0 MHz		45	50	-	dB
1670.0 ... 1675.0 MHz		40	51	-	dB
1930.0 ... 1995.0 MHz		40	53	-	dB
2110.0 ... 2170.0 MHz		40	50	-	dB
2300.0 ... 2361.0 MHz		30	34	-	dB
2361.0 ... 2690.0 MHz		30	37	-	dB
3300.0 ... 3800.0 MHz		15	20	-	dB
5150.0 ... 5850.0 MHz		5	12	-	dB

¹⁾ Error Vector Magnitude (EVM) based on definition given in 3GPP TS 25.141

SAW Components
B7939
SAW Duplexer for femtocell
782 / 751 MHz
Datasheet

Characteristics

Temperature range for specification:	$T = -10\text{ }^{\circ}\text{C to } +85\text{ }^{\circ}\text{C}$
Antenna terminating impedance:	$Z_{\text{ANT}} = 50\text{ }\Omega \parallel 16\text{ nH}$
RX terminating impedance:	$Z_{\text{RX}} = 50\text{ }\Omega$
TX terminating impedance:	$Z_{\text{TX}} = 50\text{ }\Omega$

		B7939			
Characteristics TX - ANT		min.	typ. @ 25 °C	max.	
Center frequency	f_C		751.0		MHz
Maximum insertion attenuation	α_{max}				
746.0 ... 756.0 MHz		-	1.6	2.0	dB
Amplitude ripple (p-p)	$\Delta\alpha$				
746.0 ... 756.0 MHz		-	0.4	1.0	dB
Error Vector Magnitude	EVM ¹⁾				
@ f_{carrier} 748.5 ... 753.5 MHz		-	1.4	2.5	%
Input VSWR (TX port)					
746.0 ... 756.0 MHz		-	1.5	1.8	
Output VSWR (ANT port)					
746.0 ... 756.0 MHz		-	1.4	1.8	
Attenuation	α				
10.0 ... 150.0 MHz		40	60	-	dB
150.0 ... 350.0 MHz		35	46	-	dB
350.0 ... 650.0 MHz		30	37	-	dB
698.0 ... 716.0 MHz		35	38	-	dB
716.0 ... 722.0 MHz		38	42	-	dB
777.0 ... 787.0 MHz		55	60	-	dB
788.0 ... 798.0 MHz		45	54	-	dB
798.0 ... 849.0 MHz		35	40	-	dB
1492.0 ... 1543.0 MHz		35	38	-	dB
1554.0 ... 1574.0 MHz		35	38	-	dB
1574.0 ... 1606.0 MHz		35	38	-	dB
1710.0 ... 1770.0 MHz		35	38	-	dB
1850.0 ... 1915.0 MHz		35	37	-	dB
1920.0 ... 1980.0 MHz		35	39	-	dB
2200.0 ... 2690.0 MHz		35	38	-	dB
2690.0 ... 3800.0 MHz		25	30	-	dB
5150.0 ... 5850.0 MHz		5	19	-	dB

¹⁾ Error Vector Magnitude (EVM) based on definition given in 3GPP TS 25.141

SAW Components
B7939
SAW Duplexer for femtocell
782 / 751 MHz
Datasheet

Characteristics



Temperature range for specification:	$T = -10\text{ °C to }+85\text{ °C}$
Antenna terminating impedance:	$Z_{ANT} = 50\ \Omega \parallel 16\text{ nH}$
RX terminating impedance:	$Z_{RX} = 50\ \Omega$
TX terminating impedance:	$Z_{TX} = 50\ \Omega$



				B7939			
Characteristics RX-TX				min.	typ. @ 25 °C	max.	
Attenuation							
			α				
	746.0 ...	756.0	MHz	50	55	-	dB
	777.0 ...	787.0	MHz	52	59	-	dB



Maximum Ratings

Storage temperature range	T_{stg}	-40/+85	°C	machine model, 1 pulse source and load impedance 50 Ω } LTE 5 MHz downlink average power T = 55°C, 50.000 h
DC voltage	V_{DC}	0	V	
ESD voltage	V_{ESD}	50 ¹⁾	V	
Input power at pin 1				
746.0 ...756.0 MHz	P_{in}	30.5	dBm	} average power T = 55°C, 50.000 h
elsewhere	P_{in}	10	dBm	







¹⁾ According to JESD22-A115A (machine model), 1 negative and 1 positive pulses.

Frequency Response ANT-RX

Frequency Response ANT-RX




Frequency Response TX-ANT

Frequency Response TX-ANT


Frequency Response RX-TX

Frequency Response RX-TX


Datasheet

S11 VSWR (RX)

S22 VSWR (ANT)

S33 VSWR (TX)


Datasheet

EVM RX

EVM TX


SAW Components
B7939
SAW Duplexer for femtocell
782 / 751 MHz
Datasheet

Reference

Type	B7939
Ordering code	B39781B7939P810
Marking and package	C61157-A3-A61
Packaging	F61074-V8153-Z000
Date codes	L_1126
S-parameters	B7939_NB.s3p, B7939_WB.s3p See file header for port/pin assignment table.
Soldering profile	S_6001
RoHS compatible	RoHS-compatible means that products are compatible with the requirements according to Art. 4 (substance restrictions) of Directive 2011/65/EU of the European Parliament and of the Council of June 8 th , 2011, on the restriction of the use of certain hazardous substances in electrical and electronic equipment ("Directive") with due regard to the application of exemptions as per Annex III of the Directive in certain cases.
Moldability	Before using in overmolding environment, please contact your EPCOS sales office.
Matching coils	See Inductor pdf-catalog http://www.tdk.co.jp/tefe02/coil.htm#aname1 and Data Library for circuit simulation http://www.tdk.co.jp/etvcl/index.htm

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com.

Published by EPCOS AG

Systems, Acoustics, Waves Business Group

P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2013. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CeraLink, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FilterCap, FormFit, MiniBlue, MiniCell, MKD, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.