






REV.	DESCRIPTION	DATE	APPROVED
C	Engineering Release.	08/07/12	T. Y.



DOUBLE SIDED TAPE (3X),
#6 TAPPING SCREWS (2X) INCLUDED




NOTES

1. Power Input: 24VDC, Constant Voltage
2. Power Consumption: 4.0 Watts
3. White Color Temperature: 2700K Soft White
4. Output Projection: 120° FWHM
5. Luminous Output: 160 Lumens
6. Housing Color: Black
7. Operating Temperature: 0C ~ +40C
8. For Use in Dry Locations Only



Mating Connector:
5.5 x 2.1 x 11mm DC Plug



STANDARD TOLERANCE (UNLESS OTHERWISE SPECIFIED)		 4 THOMAS, IRVINE, CA, 92618 TEL: (949) 951-8808 FAX: (949) 951-3974	
DECIMALS	ANGULAR		
.X ± .2	X° ± 1°		TITLE: B7100 SERIES LIGHT, SURFACE MOUNT, SOFT WHITE
.XX ± .02			
.XXX ± .010			
DESIGNED: Brian Oliver	DATE: 05/29/12	PART NO: B7100-S-S	REVISION: C
CHECKED: T. Yin	DATE: 05/29/12	CAGE CODE : 32559	SHEET # 1 OF 1
CAD GENERATED DOCUMENT, DO NOT MEASURE DRAWING.			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[BIVAR:](#)

[B7100-S-S](#)