



Amplifier Transistors

PNP Silicon

BC212,B
BC213
BC214



CASE 29-04, STYLE 17
TO-92 (TO-226AA)

MAXIMUM RATINGS

Rating	Symbol	BC 212	BC 213	BC 214	Unit
Collector-Emitter Voltage	V_{CEO}	-50	-30	-30	Vdc
Collector-Base Voltage	V_{CBO}	-60	-45	-45	Vdc
Emitter-Base Voltage	V_{EBO}		-5.0		Vdc
Collector Current — Continuous	I_C		-100		mAdc
Total Device Dissipation @ $T_A = 25^\circ\text{C}$ Derate above 25°C	P_D		350 2.8		mW mW/°C
Total Device Dissipation @ $T_C = 25^\circ\text{C}$ Derate above 25°C	P_D		1.0 8.0		Watts mW/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	-55 to +150			°C

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	357	°C/W
Thermal Resistance, Junction to Case	$R_{\theta JC}$	125	°C/W

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Characteristic		Symbol	Min	Typ	Max	Unit
Collector-Emitter Breakdown Voltage ($I_C = -2.0$ mAdc, $I_E = 0$)	BC212	$V_{(BR)CEO}$	-50	—	—	Vdc
	BC213		-30	—	—	
	BC214		-30	—	—	
Collector-Base Breakdown Voltage ($I_C = -10$ μ A, $I_E = 0$)	BC212	$V_{(BR)CBO}$	-60	—	—	Vdc
	BC213		-45	—	—	
	BC214		-45	—	—	
Emitter-Base Breakdown Voltage ($I_E = -10$ μ Adc, $I_C = 0$)	BC212	$V_{(BR)EBO}$	-5	—	—	Vdc
	BC213		-5	—	—	
	BC214		-5	—	—	
Collector-Emitter Leakage Current ($V_{CB} = -30$ V)	BC212	I_{CBO}	—	—	-15	nAdc
	BC213		—	—	-15	
	BC214		—	—	-15	
Emitter-Base Leakage Current ($V_{EB} = -4.0$ V, $I_C = 0$)	BC212	I_{EBO}	—	—	-15	nAdc
	BC213		—	—	-15	
	BC214		—	—	-15	

BC212,B BC213 BC214**ELECTRICAL CHARACTERISTICS** ($T_A = 25^\circ\text{C}$ unless otherwise noted) (Continued)

Characteristic	Symbol	Min	Typ	Max	Unit
ON CHARACTERISTICS					
DC Current Gain ($I_C = -10\text{ }\mu\text{A}$, $V_{CE} = -5.0\text{ Vdc}$)	h_{FE}	40	—	—	—
BC212		40	—	—	
BC213		100	—	—	
BC214		—	—	—	
($I_C = -2.0\text{ mA}$, $V_{CE} = -5.0\text{ Vdc}$)		60	—	—	
BC212		80	—	—	
BC213		140	—	600	
($I_C = -100\text{ mA}$, $V_{CE} = -5.0\text{ Vdc}$)(1)		—	120	—	
BC212, BC214		—	140	—	
Collector–Emitter Saturation Voltage ($I_C = -10\text{ mA}$, $I_B = -0.5\text{ mA}$)	$V_{CE(sat)}$	—	–0.10	—	Vdc
($I_C = -100\text{ mA}$, $I_B = -5.0\text{ mA}$)(1)		—	–0.25	–0.6	
Base–Emitter Saturation Voltage ($I_C = -100\text{ mA}$, $I_B = -5.0\text{ mA}$)	$V_{BE(sat)}$	—	–1.0	–1.4	Vdc
Base–Emitter On Voltage ($I_C = -2.0\text{ mA}$, $V_{CE} = -5.0\text{ Vdc}$)	$V_{BE(on)}$	–0.6	–0.62	–0.72	Vdc
DYNAMIC CHARACTERISTICS					
Current–Gain — Bandwidth Product ($I_C = -10\text{ mA}$, $V_{CE} = -5.0\text{ Vdc}$, $f = 100\text{ MHz}$)	f_T	—	280	—	MHz
BC212		—	320	—	
BC214		—	360	—	
Common–Base Output Capacitance ($V_{CB} = -10\text{ Vdc}$, $I_C = 0$, $f = 1.0\text{ MHz}$)	C_{ob}	—	—	6.0	pF
Noise Figure ($I_C = -0.2\text{ mA}$, $V_{CE} = -5.0\text{ Vdc}$, $R_S = 2.0\text{ k}\Omega$, $f = 1.0\text{ kHz}$)	NF	—	—	2	dB
($I_C = -0.2\text{ mA}$, $V_{CE} = -5.0\text{ Vdc}$, $R_S = 2.0\text{ k}\Omega$, $f = 1.0\text{ kHz}$, $f = 200\text{ Hz}$)		—	—	10	
Small–Signal Current Gain ($I_C = -2.0\text{ mA}$, $V_{CE} = -5.0\text{ Vdc}$, $f = 1.0\text{ kHz}$)	h_{fe}	60	—	—	—
BC212		80	—	—	
BC213		140	—	—	
BC214		200	—	400	

1. Pulse Test: T_p 300 s, Duty Cycle 2.0%.

BC212,B BC213 BC214




Figure 1. Normalized DC Current Gain




Figure 2. "Saturation" and "On" Voltages




Figure 3. Current-Gain — Bandwidth Product




Figure 4. Capacitances




Figure 5. Output Admittance






Figure 6. Base Spreading Resistance

BC212,B BC213 BC214

PACKAGE DIMENSIONS



**CASE 029-04
(TO-226AA)
ISSUE AD**

NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. DIMENSION F APPLIES BETWEEN P AND L. DIMENSION D AND J APPLY BETWEEN L AND K MINIMUM. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.175	0.205	4.45	5.20
B	0.170	0.210	4.32	5.33
C	0.125	0.165	3.18	4.19
D	0.016	0.022	0.41	0.55
F	0.016	0.019	0.41	0.48
G	0.045	0.055	1.15	1.39
H	0.095	0.105	2.42	2.66
J	0.015	0.020	0.39	0.50
K	0.500	—	12.70	—
L	0.250	—	6.35	—
N	0.080	0.105	2.04	2.66
P	—	0.100	—	2.54
R	0.115	—	2.93	—
V	0.135	—	3.43	—

STYLE 17:

1. COLLECTOR
2. BASE
3. EMITTER

Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters can and do vary in different applications. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and  are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

How to reach us:

USA/EUROPE: Motorola Literature Distribution;
P.O. Box 20912; Phoenix, Arizona 85036. 1-800-441-2447

MFAX: RMFAX0@email.sps.mot.com - TOUCHTONE (602) 244-6609
INTERNET: <http://Design-NET.com>

JAPAN: Nippon Motorola Ltd.; Tatsumi-SPD-JLDC, Toshikatsu Otsuki,
6F Seibu-Butsuryu-Center, 3-14-2 Tatsumi Koto-Ku, Tokyo 135, Japan. 03-3521-8315

HONG KONG: Motorola Semiconductors H.K. Ltd.; 8B Tai Ping Industrial Park,
51 Ting Kok Road, Tai Po, N.T., Hong Kong. 852-26629298