



Dual Digit LED Displays 16-Segment, ± 1 Overflow, 7-Segment

Digit Size	Part No.		Chip		Absolute Maximum Ratings				Electro-optical Data(At 10mA)			Drawing No.
	Common Anode	Common Cathode	Material/Emitted Color	Peak Wave Length λ_p (nm)	$\Delta \lambda$ (nm)	Pd (mw)	If (mA)	Ifp (mA)	Vf (v)		Iv. Typ. Per.Seg. (mcd)	
									Typ.	Max.		
0.52" Dual-Digit	BD-A531RD	BD-C531RD	GaAsP/Red	655	40	80	40	200	1.7	2.0	0.8	DD-19
	BD-A535RD	BD-C535RD	GaP/ Bright Red	700	90	40	15	50	2.2	2.5	1.5	
	BD-A535RE	BD-C535RE										
	BD-A532RD	BD-C532RD	GaP/ Green	568	30	80	30	150	2.2	2.5	3.5	
	BD-A533RD	BD-C533RD	GaAsP/GaP/ Yellow	585	35	80	30	150	2.1	2.5	2.5	
	BD-A534RD	BD-C534RD	GaAsP/GaP/ Hi-Eff.Red	635	45	80	30	150	2.0	2.5	3.5	
		GaAsP/GaP/ Orange										
	BD-A536RD	BD-C536RD	GaAlAs/ SH Super Red	660	20	80	30	150	1.7	2.5	6.5	
BD-A53DRD	BD-C53DRD	GaAlAs/ DH Super Red	660	20	80	30	150	1.7	2.5	7.5		
0.54" Alpha-Numeric Displays	BD-E521RD	BD-F521RD	GaAsP/Red	655	40	80	40	200	1.7	2.0	0.8	DD-20
	BD-E525RD	BD-F525RD	GaP/ Bright Red	700	90	40	15	50	2.2	2.5	1.5	
	BD-E525RE	BD-F525RE										
	BD-E522RD	BD-F522RD	GaP/ Green	568	30	80	30	150	2.2	2.5	3.5	
	BD-E523RD	BD-F523RD	GaAsP/GaP/ Yellow	585	35	80	30	150	2.1	2.5	2.5	
	BD-E524RD	BD-F524RD	GaAsP/GaP/ Hi-Eff.Red	635	45	80	30	150	2.0	2.5	3.5	
		GaAsP/GaP/ Orange										
	BD-E526RD	BD-F526RD	GaAlAs/ SH Super Red	660	20	80	30	150	1.7	2.5	6.5	
BD-E52DRD	BD-F52DRD	GaAlAs/ DH Super Red	660	20	80	30	150	1.7	2.5	7.5		
0.56" Dual-Digit	BD-A511RD	BD-C511RD	GaAsP/Red	655	40	80	40	200	1.7	2.0	0.8	DD-21
	BD-A515RD	BD-C515RD	GaP/ Bright Red	700	90	40	15	50	2.2	2.5	1.5	
	BD-A515RE	BD-C515RE										
	BD-A512RD	BD-C512RD	GaP/ Green	568	30	80	30	150	2.2	2.5	3.5	
	BD-A513RD	BD-C513RD	GaAsP/GaP/ Yellow	585	35	80	30	150	2.1	2.5	2.5	
	BD-A514RE	BD-C514RE	GaAsP/GaP/ Hi-Eff.Red	635	45	80	30	150	2.0	2.5	3.5	
		GaAsP/GaP/ Orange										
	BD-A516RD	BD-C516RD	GaAlAs/ SH Super Red	660	20	80	30	150	1.7	2.5	6.5	
BD-A51DRD	BD-C51DRD	GaAlAs/ DH Super Red	660	20	80	30	150	1.7	2.5	7.5		
0.56" Dual-Digit	BD-A541RD	BD-C541RD	GaAsP/Red	655	40	80	40	200	1.7	2.0	0.9	DD-22
	BD-A545RD	BD-C545RD	GaP/ Bright Red	700	90	40	15	50	2.2	2.5	1.6	
	BD-A545RE	BD-C545RE										
	BD-A542RD	BD-C542RD	GaP/ Green	568	30	80	30	150	2.2	2.5	3.8	
	BD-A543RD	BD-C543RD	GaAsP/GaP/ Yellow	585	35	80	30	150	2.1	2.5	2.8	
	BD-A544RE	BD-C544RE	GaAsP/GaP/ Hi-Eff.Red	635	45	80	30	150	2.0	2.5	3.6	
		GaAsP/GaP/ Orange										
	BD-A546RD	BD-C546RD	GaAlAs/ SH Super Red	660	20	80	30	150	1.7	2.5	6.8	
	BD-A54DRD	BD-C54DRD	GaAlAs/ DH Super Red	660	20	80	30	150	1.7	2.5	7.8	
	BD-E541RD	BD-F541RD	GaAsP/Red	655	40	80	40	200	1.7	2.0	0.9	DD-23
	BD-E545RD	BD-F545RD	GaP/ Bright Red	700	90	40	15	50	2.2	2.5	1.6	
	BD-E545RE	BD-F545RE										
	BD-E542RD	BD-F542RD	GaP/ Green	568	30	80	30	150	2.2	2.5	3.8	
BD-E543RD	BD-F543RD	GaAsP/GaP/ Yellow	585	35	80	30	150	2.1	2.5	2.8		
BD-E544RE	BD-F544RE	GaAsP/GaP/ Hi-Eff.Red	635	45	80	30	150	2.0	2.5	3.6		
	GaAsP/GaP/ Orange											
BD-E546RD	BD-F546RD	GaAlAs/ SH Super Red	660	20	80	30	150	1.7	2.5	6.8		
BD-E54DRD	BD-F54DRD	GaAlAs/ DH Super Red	660	20	80	30	150	1.7	2.5	7.8		



Dual Digit LED Displays 16-Segment, ± 1 Overflow, 7-segment

DD-19 BD- $\overset{A}{\underset{C}{53}}$xRD DD-19 BD- $\overset{A}{\underset{C}{53}}$xRD	DD-20 BD- $\overset{E}{\underset{F}{52}}$xRD DD-20 BD- $\overset{E}{\underset{F}{52}}$xRD
DD-21 BD- $\overset{A}{\underset{C}{51}}$xRD DD-21 BD- $\overset{A}{\underset{C}{51}}$xRD	DD-22 BD- $\overset{A}{\underset{C}{54}}$xRD DD-22 BD- $\overset{A}{\underset{C}{54}}$xRD
DD-23 BD- $\overset{E}{\underset{F}{54}}$xRD DD-23 BD- $\overset{E}{\underset{F}{54}}$xRD	

NOTES: 1.ALL Dimensions are in millimeters(inches).
3.Specifications are subject to change without notice.

2.Tolerance is $\pm 0.25\text{mm}(.010")$
4.NP:No Pin. 5.NC:No Connect

AMERICAN BRIGHT

www.americanbrightled.com

DSP-41

(909) 628-5050 FAX (909) 628-5006 • © 2003 American Bright Optoelectronics Corporation. Specifications subject to change without notice.