


LAMINATED TRANSFORMERS

Type EI48 / 16.8 - 10VA




- ⊕ Frequency 50/60Hz
- ⊕ Potted under vacuum
- ⊕ Split-bobbin
- ⊕ Temperature class ta 40°C/B
- ⊕ Weight: 0.295kg
- ⊕ Packaging unit: 15 pieces (tray)

Mechanical



Schematics



| Primary (V) | Secondary (V / mA) | No-Load Voltage (V) | Schematic No. | Part Number | Agency Approvals |
|-------------|--------------------|---------------------|---------------|-------------|------------------|
| 230 | 6 / 1666 | 7.90 | 1 | 048-5187.0 | 1/3* |
| 230 | 9 / 1111 | 12.00 | 1 | 048-5190.0 | 1/3* |
| 230 | 12 / 834 | 15.70 | 1 | 048-5193.0 | 1/3* |
| 230 | 15 / 666 | 19.20 | 1 | 048-5196.0 | 1/3* |
| 230 | 18 / 555 | 22.90 | 1 | 048-5199.0 | 1/3* |
| 230 | 24 / 416 | 30.60 | 1 | 048-5205.0 | 1/3* |
| 230 | 2x6 / 834 | 2x8.10 | 2 | 048-5210.0 | 1/3* |
| 230 | 2x9 / 555 | 2x11.60 | 2 | 048-5213.0 | 1/3* |
| 230 | 2x12 / 416 | 2x15.70 | 2 | 048-5216.0 | 1/3* |
| 230 | 2x15 / 333 | 2x19.50 | 2 | 048-5219.0 | 1/3* |
| 230 | 2x18 / 277 | 2x23.50 | 2 | 048-5222.0 | 1/3* |
| 230 | 2x24 / 208 | 2x30.00 | 2 | 048-5228.0 | 1 |
| 115 | 6 / 1666 | 7.90 | 1 | 048-5049.0 | 1/3* |
| 115 | 9 / 1111 | 12.00 | 1 | 048-5052.0 | 1/3* |
| 115 | 12 / 834 | 15.70 | 1 | 048-5055.0 | 1/3* |
| 115 | 15 / 666 | 19.20 | 1 | 048-5058.0 | 1/3* |
| 115 | 18 / 555 | 22.90 | 1 | 048-5061.0 | 1/3* |
| 115 | 24 / 416 | 30.60 | 1 | 048-5067.0 | 1/3* |
| 115 | 2x6 / 834 | 2x8.10 | 2 | 048-5072.0 | 1/3* |
| 115 | 2x9 / 555 | 2x11.60 | 2 | 048-5075.0 | 1/3* |
| 115 | 2x12 / 416 | 2x15.70 | 2 | 048-5078.0 | 1/3* |
| 115 | 2x15 / 333 | 2x19.50 | 2 | 048-5081.0 | 1/3* |
| 115 | 2x18 / 277 | 2x23.50 | 2 | 048-5084.0 | 1/3* |
| 115 | 2x24 / 208 | 2x30.00 | 2 | 048-5090.0 | 1 |
| 2x115 | 6 / 1666 | 7.90 | 3 | 048-5325.0 | 1/3* |
| 2x115 | 9 / 1111 | 12.00 | 3 | 048-5328.0 | 1/3* |
| 2x115 | 12 / 834 | 15.70 | 3 | 048-5331.0 | 1/3* |
| 2x115 | 15 / 666 | 19.20 | 3 | 048-5334.0 | 1/3* |
| 2x115 | 18 / 555 | 22.90 | 3 | 048-5337.0 | 1/3* |
| 2x115 | 24 / 416 | 30.60 | 3 | 048-5343.0 | 1/3* |
| 2x115 | 2x6 / 834 | 2x8.10 | 4 | 048-5348.0 | 1/3* |
| 2x115 | 2x9 / 555 | 2x11.60 | 4 | 048-5351.0 | 1/3* |
| 2x115 | 2x12 / 416 | 2x15.70 | 4 | 048-5354.0 | 1/3* |
| 2x115 | 2x15 / 333 | 2x19.50 | 4 | 048-5357.0 | 1/3* |
| 2x115 | 2x18 / 277 | 2x23.50 | 4 | 048-5360.0 | 1/3* |
| 2x115 | 2x24 / 208 | 2x30.00 | 4 | 048-5366.0 | 1 |

*NOTE: When checking the approval status of this product with VDE, add the prefix "BV" and the suffix "H" to the orderable Part Number (these letters will also be found on the part label). The prefix and suffix are not part of the orderable Part Number.