


**Rectifier diode  
ultrafast, low switching loss**

**BYC8B-600**

**FEATURES**

- Extremely fast switching
- Low reverse recovery current
- Low thermal resistance
- Reduces switching losses in associated MOSFET

**SYMBOL**



**QUICK REFERENCE DATA**

|                               |
|-------------------------------|
| $V_R = 600\text{ V}$          |
| $V_F \leq 1.85\text{ V}$      |
| $I_{F(AV)} = 8\text{ A}$      |
| $t_{rr} = 19\text{ ns (typ)}$ |

**APPLICATIONS**


- Active power factor correction
- Half-bridge lighting ballasts
- Half-bridge/ full-bridge switched mode power supplies.

The BYC8B-600 is supplied in the SOT404 surface mounting package.

**PINNING**

| PIN | DESCRIPTION          |
|-----|----------------------|
| 1   | no connection        |
| 2   | cathode <sup>1</sup> |
| 3   | anode                |
| tab | cathode              |

**SOT404**



**LIMITING VALUES**

Limiting values in accordance with the Absolute Maximum System (IEC 134).

| SYMBOL      | PARAMETER                            | CONDITIONS   | MIN. | MAX.     | UNIT   |
|-------------|--------------------------------------|--|------|----------|--------|
| $V_{RRM}$   | Peak repetitive reverse voltage      |  | -    | 600      | V      |
| $V_{RWM}$   | Crest working reverse voltage        |  | -    | 600      | V      |
| $V_R$       | Continuous reverse voltage           | $T_{mb} \leq 110\text{ °C}$  | -    | 500      | V      |
| $I_{F(AV)}$ | Average forward current              | $\delta = 0.5$ ; with reapplied $V_{RRM(max)}$ ;<br>$T_{mb} \leq 82\text{ °C}$   | -    | 8        | A      |
| $I_{FRM}$   | Repetitive peak forward current      | $\delta = 0.5$ ; with reapplied $V_{RRM(max)}$ ;<br>$T_{mb} \leq 82\text{ °C}$   | -    | 16       | A      |
| $I_{FSM}$   | Non-repetitive peak forward current. | $t = 10\text{ ms}$<br>$t = 8.3\text{ ms}$<br>sinusoidal; $T_j = 150\text{ °C}$ prior to surge<br>with reapplied $V_{RWM(max)}$ | -    | 55<br>60 | A<br>A |
| $T_{stg}$   | Storage temperature                  |  | -40  | 150      | °C     |
| $T_j$       | Operating junction temperature       |  | -    | 150      | °C     |

**THERMAL RESISTANCES**

| SYMBOL         | PARAMETER                                    | CONDITIONS                   | MIN. | TYP. | MAX. | UNIT |
|----------------|--|------------------------------|------|------|------|------|
| $R_{th\ j-mb}$ | Thermal resistance junction to mounting base |                              | -    | -    | 2.2  | K/W  |
| $R_{th\ j-a}$  | Thermal resistance junction to ambient       | minimum footprint, FR4 board | -    | 50   | -    | K/W  |

<sup>1</sup> it is not possible to make connection to pin 2 of the SOT404 package





Rectifier diode  
ultrafast, low switching loss

BYC8B-600

**ELECTRICAL CHARACTERISTICS**







$T_j = 25\text{ }^\circ\text{C}$  unless otherwise stated

| SYMBOL    | PARAMETER                     | CONDITIONS   | MIN. | TYP.              | MAX.               | UNIT                |
|-----------|-------------------------------|--|------|-------------------|--------------------|---------------------|
| $V_F$     | Forward voltage               | $I_F = 8\text{ A}; T_j = 150\text{ }^\circ\text{C}$<br>$I_F = 16\text{ A}; T_j = 150\text{ }^\circ\text{C}$<br>$I_F = 8\text{ A};$ | -    | 1.4<br>1.7<br>2.0 | 1.85<br>2.3<br>2.8 | V<br>V<br>V         |
| $I_R$     | Reverse current               | $V_R = 600\text{ V}$<br>$V_R = 500\text{ V}; T_j = 100\text{ }^\circ\text{C}$  | -    | 9<br>1.1          | 150<br>3.0         | $\mu\text{A}$<br>mA |
| $t_{rr}$  | Reverse recovery time         | $I_F = 1\text{ A}; V_R = 30\text{ V}; dI_F/dt = 50\text{ A}/\mu\text{s}$   | -    | 30                | 52                 | ns                  |
| $t_{rr}$  | Reverse recovery time         | $I_F = 8\text{ A}; V_R = 400\text{ V};$<br>$dI_F/dt = 500\text{ A}/\mu\text{s}$  | -    | 19                | -                  | ns                  |
| $t_{rr}$  | Reverse recovery time         | $I_F = 8\text{ A}; V_R = 400\text{ V};$<br>$dI_F/dt = 500\text{ A}/\mu\text{s}; T_j = 125\text{ }^\circ\text{C}$                   | -    | 32                | 40                 | ns                  |
| $I_{rrm}$ | Peak reverse recovery current | $I_F = 8\text{ A}; V_R = 400\text{ V};$<br>$dI_F/dt = 50\text{ A}/\mu\text{s}; T_j = 125\text{ }^\circ\text{C}$                    | -    | 1.5               | 5.5                | A                   |
| $I_{rrm}$ | Peak reverse recovery current | $I_F = 8\text{ A}; V_R = 400\text{ V};$<br>$dI_F/dt = 500\text{ A}/\mu\text{s}; T_j = 125\text{ }^\circ\text{C}$                   | -    | 9.5               | 12                 | A                   |
| $V_{fr}$  | Forward recovery voltage      | $I_F = 10\text{ A}; dI_F/dt = 100\text{ A}/\mu\text{s}$  | -    | 8                 | 10                 | V                   |



Rectifier diode  
ultrafast, low switching loss

BYC8B-600



Rectifier diode  
ultrafast, low switching loss

BYC8B-600




Fig.9. Definition of reverse recovery parameters  $t_{rr}$ ,  $I_{rrm}$




Fig.12. Typical and maximum forward characteristic  $I_F = f(V_F)$ ;  $T_j = 25^\circ\text{C}$  and  $150^\circ\text{C}$ .




Fig.10. Typical forward recovery voltage  $V_{fr}$  as a function of rate of change of current  $dI_F/dt$ .




Fig.13. Typical reverse leakage current as a function of reverse voltage.  $I_R = f(V_R)$ ; parameter  $T_j$




Fig.11. Definition of forward recovery voltage  $V_{fr}$





Fig.14. Maximum thermal impedance  $Z_{th j-mb}$  as a function of pulse width.


Rectifier diode  
ultrafast, low switching loss

BYC8B-600

**MECHANICAL DATA**



**MOUNTING INSTRUCTIONS**



**Notes**

- 1. Epoxy meets UL94 V0 at 1/8".

## Rectifier diode ultrafast, low switching loss

BYC8B-600

### DEFINITIONS

|  |   |
|--|---|
| <b>Data sheet status</b>   |   |
| Objective specification  | This data sheet contains target or goal specifications for product development.       |
| Preliminary specification  | This data sheet contains preliminary data; supplementary data may be published later. |
| Product specification  | This data sheet contains final product specifications.                                |
| <b>Limiting values</b>   |   |
| Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability. |   |
| <b>Application information</b>   |   |
| Where application information is given, it is advisory and does not form part of the specification.  |   |
| © Philips Electronics N.V. 1999  |   |
| All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.  |   |
| The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.   |   |

### LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.