


Capacitor, Ceramic, SMD, MLCC, FF-CAP, Floating Electrode, Automotive Grade, 0.022 uF, +/-10% Tol, 100 V, X7R, 0805 (2012 metric)



General Information

Supplier:	KEMET
Application:	Automotive/Floating Electrode (AEC-Q200 Qualified)
Chip Size:	0805 (2012 metric)
Temperature Coefficient:	X7R
Part Type Description:	SMD, MLCC, FF-CAP, Floating Electrode, Automotive Grade
Termination Type:	Flexible Termination
Marked:	No
RoHS:	Yes
Approvals:	AEC-Q200

Dimensions (mm)

Symbol	Dimension	Tolerance
L	2	+/-0.3
W	1.25	+/-0.3
T	0.9	+/-0.10
B	0.5	+/-0.25
S	0.75	MIN

Packaging Specifications

Package Kind:	T&R
Package Size:	7 in/180 mm
Package Type:	Plastic Tape
Package Quantity:	4000

Specifications

Capacitance:	0.022 uF
Voltage:	100 V
Tolerance:	+/-10%
Temperature Range:	-55/+125C
Dissipation Factor:	2.5%
Failure Rate:	N/A
Aging Rate:	3% loss/decade hour
Insulation Resistance:	45.45 GOhm
Dielectric Strength:	250 V
Miscellaneous:	Note: Referee time for X7R dielectric for this part number is 1000 hours