

# 7000 Push Button Switches 16A 250Vac



- ▶ Round and rectangular **ARCOSwitches.com**  
THE ONLINE DISTRIBUTOR OF ELECTRONIC COMPONENTS
- ▶ Ratings up to 16A, 250V ac
- ▶ Latching and momentary
- ▶ Illuminated & non-illuminated
- ▶ Matching indicators
- ▶ Low profile version
- ▶ Panel cut outs:  
25.0 dia  
27.2 x 22.3



16(4)A 250Vac T125  
8(8)A 250Vac T85



UL CSA 16A Non Ind, 250Vac 1hp, 125Vac 1/2hp  
UL 65°C, file no. E45221, CSA file no. LR10990



RoHS compliant

3mm contact gap.  
Technical data on pages 4 & 5 (switches), 6 (indicators).

**C 7053 A F ---**

TERMINAL    FUNCTION    ROCKER    BODY    PRINT, COLOUR, ETC

push switches

TERMINAL	FUNCTION		ACTUATOR
<b>C</b>  6.3 x 0.8 9.1	<b>7000</b>	 Single pole ON - OFF	<b>A</b> Round actuator shown in F body  21.0 9.7 <b>A</b> Round actuator shown in G body  <b>B</b> Round actuator - medium shown in F body  21.1 11.5 18.6 <b>C</b> Round actuator - long shown in F body  21.1 11.2 20.0 29.5 <b>D</b> Round actuator - sub panel mount  21.1 16.9 <b>S</b> Rectangular actuator Shown in "A" body N/A for 7030  19.5 8.8
	<b>7001</b>	 Single pole ON - OFF (momentary ON)	
	<b>7003</b>	 Single pole ON - OFF with light	
	<b>7004</b>	 Single pole ON - OFF (momentary ON) with light	
	<b>7050</b>	 Double pole ON - OFF	
	<b>7051</b>	 Double pole ON - OFF (momentary ON)	
	<b>7053</b>	 Double pole ON - OFF with light	
<b>H</b>  4.8 x 0.8 9.1	<b>7054</b>	 Double pole ON - OFF (momentary ON) with light	
	<b>7030</b>	 Indicator 	



C7000AF ---




C7003AF ---



C7053CF ---



C7053BF ---



C7050SA ---



C7053AG ---



C7053DF ---





C7030AH ---


**BODY**

Panel cut-outs

**F H G** Body types fit either cut-out



**A**



Cut-outs must be punched in the direction of insertion

**OPTIONS**

**Finish**

Matt finish is standard on bodies.  
Gloss finish is standard on actuators.

**Colour**

Call sales for custom colours.  
A full range is available for large orders.

**Legend printing**

A wide range is available or call sales for custom legends.

**Lamp voltage**

Call sales for details of available voltages.

**Protective housing (E)**

(designed to IP65)  
Covers are available for round body styles, call sales for details.

**DIMENSIONS (mm)**

**Panel thickness:**

**A** 0.8 - 2.5mm

**F, G, H** 0.8 - 5.0mm

