

DETAILS

Product Number	CA13753_STRADA-SQ-FW
Family	Strada-Forward
Type	Assembly
Color	clear
Diameter	25 + 25 mm
Height	15,4 mm
Style	square
Optic Material	PMMA
Holder Material	
Fastening	pin, screw, tape
Status	production ready
ROHS Compliant	Yes
Date Updated	11/01/2016



OPTICAL PROPERTIES

LED	Viewing Angle	Light Beam	Efficiency	cd/lm	Connector
MK-R	Asymmetric deg	Asymmetric	sim: 89 %	-	-
XHP50	Asymmetric deg	Asymmetric	92 %	0.670	-
LUXEON M	Asymmetric deg	Asymmetric	89 %	0.615	-
LUXEON MZ	asymmetric deg	Asymmetric	90 %	0.730	-
LUXEON XR-M linear 1x3, 1x4, 1x5	Asymmetric deg	Asymmetric	90 %	0.620	-
Duris S10	Asymmetric deg	Asymmetric	89 %	0.590	-
Duris P10	sim: Asymmetric	Asymmetric	sim: 91 %	sim: 1.100	-

D


C

B


A

4


4




Isometric view




Bottom view



Front view



Top view



INDEX	PART NO	DESCRIPTION	MATERIAL	COLOUR
1	CA13753	STRADA-SQ-FW	PMMA / PU double sided tape	

Tolerances if not otherwise shown
According to DIN ISO 2768-1
Linear measures:
Up to 30mm class M, otherwise class C.
According to DIN ISO 2768-2
Form and position: class L

Ledil Oy
Salorankatu 10
FIN 24240 SALO
Finland

THIRD ANGLE PROJECTION:	DRAWING TITLE			
	CA13753_STRADA-SQ-FW			
	SIZE	PART NUMBER		
A4		CA13753		
SCALE		1:1	WEIGHT	- g
			SHEET	1 / 1

D

C

B

A

4

4

3

3

2

2


1

1


D

A


Luminaire: LEDiL Oy CA13753_STRADA-SQ-FW_(XHP50_cool_white)
Lamps: 1 x CREE_XHP50_cool_white_246.221lm@250mA_P=1.42945W_I=249.9mA



Luminaire: LEDiL Oy CA13753_STRADA-FW_(Luxeon_M)
Lamps: 1 x Luxeon_M_349.375lm@250mA_CCT=4092K_P=2.72866W_I=249.9mA




Luminaire: LEDiL Oy CA13753_STRADA-SQ-FW_(Luxeon_MZ) Eff: 90%
Lamps: 1 x LUXEON-MZ_263.073lm@250mA_P=2.7399W_I=249.9mA




Luminaire: Ledil CA13753_STRADA-SQ-FW_(LUXEON_XR-M_Linear_1x4)

Lamps: 1 x Lumiled_LUXEON_XR-M_Linear_1x4_1798.32lm@250mA_P=11.005W_I=0.25A




Luminaire: Ledil CA13753_STRADA-SQ-FW_(Duris_S10)

Lamps: 1 x Osram_Duris_S10_(GW-P7LP32.EM)_992.375lm@250mA_P=9.2362W_I=0.25A




Luminaire: LEDiL Oy CA13753_STRADA-SQ-FW_(XHP50_cool_white)

Lamps: 1 x CREE_XHP50_cool_white_246.221lm@250mA_P=1.42945W_I=249.9mA




Luminaire: LEDiL Oy CA13753_STRADA-FW_(Luxeon_M)

Lamps: 1 x Luxeon_M_349.375lm@250mA_CCT=4092K_P=2.72866W_I=249.9mA




Luminaire: LEDiL Oy CA13753_STRADA-SQ-FW_(Luxeon_MZ) Eff: 90%
Lamps: 1 x LUXEON-MZ_263.073lm@250mA_P=2.7399W_I=249.9mA



Luminaire: Ledil CA13753_STRADA-SQ-FW_(LUXEON_XR-M_Linear_1x4)

Lamps: 1 x Lumiled_LUXEON_XR-M_Linear_1x4_1798.32lm@250mA_P=11.005W_I=0.25A



cd/klm


— C0 - C180

— C90 - C270

$\eta = 91\%$

Luminaire: Ledil CA13753_STRADA-SQ-FW_(Duris_S10)

Lamps: 1 x Osram_Duris_S10_(GW-P7LP32.EM)_992.375lm@250mA_P=9.2362W_I=0.25A



NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.