



JKL PART NUMBER	- A - LENGTH	COLOR 5000 °k	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
CF26346-37B	346±3.0	x = .345±.01 y = .360±.01	1450	700	6± 1	36,000±15%	40,000
CF26397-37B	397±3.0		1520	725			
CF26448-37B	448±3.0		1820	870			
CF26499-37B	499±3.0		2100	1000			
CF26550-37B	550±3.0		2270	1100			
CF26600-37B	600±3.0		2340	1125			

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC		DIMENSIONS ARE IN MILLIMETERS		JKL COMPONENTS CORPORATION				
			TOLERANCE UNLESS OTHERWISE SPECIFIED		TITLE						
			1 PL +/- 0.2		MINIATURE COLD CATHODE FLUORESCENT LAMP						
			2 PL +/- 0.20								
THIRD ANGLE PROJECTION		TOLERANCE UNLESS OTHERWISE SPECIFIED		1 PL +/- 0.2		2 PL +/- 0.20		ANGLE +/- 0			
DRAWN BY		APPV'D BY		DATE		SIZE		FSCM NO.		DRAWING NO.	
L. WENGSTROM		J.K.		11/18/04		A		55335		CF 26-37B	
CHANGE LENGTH & PART NO.		11/18/04		11/17/04		- CAD DRAWING -		SCALE		RELEASED DATE	
RELEASE & CANCEL P-0410-05		11/17/04		APPV'D DATE		MANUAL REVISIONS NOT PERMITTED		NONE		11/17/04	
DESCRIPTION/ECO NUMBER		11/17/04		11/18/04		A		SHEET 1 OF 1			

Downloaded from Elcodis.com electronic components distributor