Fuse Blocks, 5 x 20 and 5 x 25 mm

Altech fuse terminals are also available with light indication - CF4U(L). A specially designed built-in circuit gives light indication in the event of fuse blow out. Thus, fault in a circuit can be easily located. No polarity is required.

Important:
The disconnecting device is not suitable for interrupting load. The supply must be switched off before operating the slide link/lever.

† Fuses are sold separately see pages 100-101.

* Add required voltage to part number as a suffix. i.e. CF4U(L)/6-60 for 6-60 V AC/DC.



	CF4U†			CF4U(L)†*		
				 No Polarity Required.		
Terminal Width	8 mm			8 mm		
Height x Length	57.6 x 57 mm			57.6 x 57 mm		
Stripping Length	9.5 mm			9.5 mm		
Insulation Material	Polyamide 6.6			Polyamide 6.6		
Type of Connection	4 screw clamps			4 screw clamps		
LED Voltage 6-60 V AC/DC 90-240 V AC/DC				CF4U(L)/6-60 CF4U(L)/90-240		
Type of Fuse Used	**Ø5x20, Ø5x25 mm**			**Ø5x20, Ø5x25 mm**		
Approvals	CSA C US	IEC 60947-7-3	UL C US E220514	CSA C US	IEC 60947-7-3	UL C US E220514
Wire Range	22-10 AWG	0.2-4 mm²	22-10 AWG	22-10 AWG	0.2-4 mm²	22-10 AWG
Voltage Rating	600 V	1000 V	600 V	600 V	600 V	600 V
Current Rating	10 A	6.3 A	10 A	10 A	6.3 A	10 A
Torque	7 lb-in	0.5 Nm	7 lb-in	7 lb-in	0.5 Nm	7 lb-in
Other Approvals	RoHS CE			RoHS CE		

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Terminal Block	**CF4U**	100	**CF4U(L)***	50
DIN Rail for ordering information refer to pages 90-91				
End Stop for ordering information refer to page 92	CA702 CA802	50 50	CA702 CA802	50 50
Internal Jumper 2 pole 3 pole 4 pole 10 pole			CF4U(L) Only  LED Circuit for offline indication in CF4U(L)/6-60V	
Insulated Internal Jumper 2 pole 3 pole 4 pole 10 pole			 LED Circuit for offline indication in CF4U(L)/90-240V	
Current Bar 2 pole 3 pole 4 pole 10 pole 				
Shorting Sleeve & Screw				
External Jumper 2 pole 3 pole 4 pole 10 pole	CA711/2 CA711/3 CA711/4 CA711/10	100 50 50 20	CA711/2 CA711/3 CA711/4 CA711/10	100 50 50 20
Marking Tags (on terminal) (on Lever)	MT8 MT8	100 100	MT8 MT8	100 100

COLOR BLOCKS
(other than standard grey)

When ordering please add color suffix to Cat. No.

Example for color Red: ***Cat.No./R***

Color	Ordering Suffix
Red	R
Yellow	Y
Blue	BU
Green	G
Consult Altech for availability:	
Orange	O
Beige	BG
Dark Brown	DB
Black	BL
White	W

Altech Corp.® • 35 Royal Road • Flemington, NJ 08822-6000 • Phone (908)806-9400 • FAX (908)806-9490 • www.altechcorp.com