

NOTES:

A

-
4. DIMENSIONS IN PARENTHESES ARE IN METRIC.
- Dimensions (Inches / Millimeters):
- Overall Length: 19.00 [482.6]
 - Overall Width: 2.80 [71.1]
 - Top Flange Thickness: .44 [11.2]
 - Top Flange Width: 17.25 [438.2]
 - Top Flange Hole Diameter: .88 [22.2]
 - Top Flange Hole Position: 3.91 [99.4] (from right edge), 3.55 [90.2] (from centerline)
 - Top Flange Hole Spacing: 1.40 [35.6] (between holes)
 - Top Flange Hole Diameter: 1.75 [44.4]
 - Top Flange Hole Position: .40 [10.2] (from left edge)
 - Top Flange Hole Diameter: .40 [10.2]
- CAD FILENAME/LAYERS: M00673BB_DC_00B.PRT

CAD FILENAME/LAYERS

M00673BB_DC_00B.PRT

PANDUIT CORP. TINLEY PARK, ILLINOIS

2 RACK UNIT - FIBER ADAPTER PATCH PANEL
(CFAPPBL2) CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:
(.X) $\pm .13(3.3)$ (.XXX) $\pm$
(.XX) $\pm .03(.8)$ ANGLES $\pm$

UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE GIVEN
IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY BAS

DATE	6-30-00
------	---------

CHK'D	AFW
-------	-----

MAT'L:

16 GA. C.R.S.

SCALE	NONE
-------	------

DRAWING NO.

00673-17

DWG
A
SIZE

1	5-2-02	JDWE		A. REVISED NOTE 3- ADDED METRIC SCREWS	00673-17				
R	6-30-00	BAS	AFW	RELEASED TO PRODUCTION	00673-17		AFW		
REV	DATE	BY	CHK	DESCRIPTION	ECN - R	CUST	SUP		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

CFAPPBL2