

ADURA Module P/N	Typical Wattage (W)	OPERATING CURRENT		INPUT VOLTAGE (Vdc)	CCT (Kelvin)	CRI	TYPICAL LUMEN (lm)	Typical Lumens Per Watt (LPW)	DIMENSIONS (mm)
		Nominal Current (mA)	Max Current (mA)						
CIR-15009D-033535-277-1x3	3	350	1500	8.4	2700K	70	434	148	0.807 inch Diameter
	4	500		8.6			601	140	
	6	700		8.8			808	131	
	9	1000		9.1			1089	120	
	11	1200		9.3			1262	113	
CIR-15009D-033535-307-1x3	3	350	1500	8.4	3000K	70	445	152	
	4	500		8.6			616	144	
	6	700		8.8			828	135	
	9	1000		9.1			1116	123	
	11	1200		9.3			1294	116	
CIR-15009D-033535-357-1x3	3	350	1500	8.4	3500K	70	461	157	
	4	500		8.6			638	149	
	6	700		8.8			858	139	
	9	1000		9.1			1156	127	
	11	1200		9.3			1340	120	
CIR-15009D-033535-407-1x3	3	350	1500	8.4	4000K	70	505	173	
	4	500		8.6			699	163	
	6	700		8.8			940	153	
	9	1000		9.1			1267	139	
	11	1200		9.3			1469	132	
CIR-15009D-033535-457-1x3	3	350	1500	8.4	4500K	70	506	173	
	4	500		8.6			702	164	
	6	700		8.8			943	153	
	9	1000		9.1			1271	140	
	11	1200		9.3			1473	132	
CIR-15009D-033535-507-1x3	3	350	1500	8.4	5000K	70	508	174	
	4	500		8.6			704	164	
	6	700		8.8			948	154	
	9	1000		9.1			1282	141	
	11	1200		9.3			1488	134	
CIR-15009D-033535-577-1x3	3	350	1500	8.4	5700K	70	486	166	
	4	500		8.6			673	157	
	6	700		8.8			906	147	
	9	1000		9.1			1226	135	
	11	1200		9.3			1423	128	
CIR-15009D-033535-657-1x3	3	350	1500	8.4	6500K	70	479	164	
	4	500		8.6			664	155	
	6	700		8.8			895	145	
	9	1000		9.1			1210	133	
	11	1200		9.3			1405	126	
CIR-15009D-033535-278-1x3	3	350	1500	8.4	2700K	80	401	137	0.807 inch Diameter
	4	500		8.6			555	130	
	6	700		8.8			746	121	
	9	1000		9.1			1005	111	
	11	1200		9.3			1166	105	
CIR-15009D-033535-308-1x3	3	350	1500	8.4	3000K	80	423	144	
	4	500		8.6			586	137	
	6	700		8.8			787	128	
	9	1000		9.1			1061	117	
	11	1200		9.3			1230	111	
CIR-15009D-033535-358-1x3	3	350	1500	8.4	3500K	80	442	151	
	4	500		8.6			612	143	
	6	700		8.8			822	134	
	9	1000		9.1			1108	122	
	11	1200		9.3			1285	116	
CIR-15009D-033535-408-1x3	3	350	1500	8.4	4000K	80	445	152	
	4	500		8.6			616	144	
	6	700		8.8			828	135	
	9	1000		9.1			1116	123	
	11	1200		9.3			1294	116	
CIR-15009D-033535-458-1x3	3	350	1500	8.4	4500K	80	449	154	
	4	500		8.6			623	146	
	6	700		8.8			837	136	
	9	1000		9.1			1128	124	
	11	1200		9.3			1308	118	
CIR-15009D-033535-508-1x3	3	350	1500	8.4	5000K	80	441	151	
	4	500		8.6			612	143	
	6	700		8.8			824	134	
	9	1000		9.1			1114	123	
	11	1200		9.3			1294	116	

CIR-15009D-033535-279-1x3	3	350	1500	8.4	2700K	90	270	92	0.807 inch Diameter
	4	500		8.6			376	88	
	6	700		8.8			504	82	
	9	1000		9.1			679	75	
	11	1200		9.3			788	71	
CIR-15009D-033535-309-1x3	3	350	1500	8.4	3000K	90	292	100	
	4	500		8.6			405	95	
	6	700		8.8			544	89	
	9	1000		9.1			732	81	
	11	1200		9.3			851	76	
CIR-15009D-033535-359-1x3	3	350	1500	8.4	3500K	90	310	106	
	4	500		8.6			431	101	
	6	700		8.8			578	94	
	9	1000		9.1			778	86	
	11	1200		9.3			904	81	
CIR-15009D-033535-407-1x3	3	350	1500	8.4	4000K	90	322	110	
	4	500		8.6			448	105	
	6	700		8.8			601	98	
	9	1000		9.1			809	89	
	11	1200		9.3			940	84	