


A. Electrical Specifications ( $T_a = +25^{\circ}\text{C}$ )


1. Rated Voltage:  
250V AC 50/60 Hz
2. Rated Current: 0.2A AC
3. Inductance (@ 1 KHz 1V): 33 mH MIN
4. Insulation Resistance:  
DC 500V 100M $\Omega$  MIN  
Between Winding to Winding  
Between Winding to Core
5. Hi-Pot Test:  
Winding to Winding AC 2.0 KV  
Winding to Core
6. DC Resistance: 5.4 $\Omega$  MAX

## B. Marking; 0330 and date code

## C. Schematic Diagram:



## D. Mechanical Specifications:



## TOLERANCES (mm)

|              |           |
|--------------|-----------|
| $\leq 4$     | $\pm 0.2$ |
| $4 \leq 20$  | $\pm 0.3$ |
| $20 \leq 50$ | $\pm 0.4$ |

PREPARED BY:

K. Brennan

ENGINEER:

T. Shiozawa

QUALITY CONTROL:

V. Casey

APPROVED:

V. Casey

DWG CONTROL NO.

P-A4-11524

ACAD\MXFMR\A4115241.DWG

REV

—

COIL

COMMON MODE

CMF-0330

MODEL SPECIFICATION

TAMURA CORPORATION OF AMERICA

43352 BUSINESS PARK DRIVE, TEMECULA, CA. 92590-6624  
(909) 699-1270 FAX 9096769482

DIM: mm(In) SCL: 2/1 SH: 1 OF 1

PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Tamura:](#)

[CMF-0330](#)