


SERIES: CP60 | DESCRIPTION: 6.0 A PELTIER MODULE
FEATURES

- solid state device
- small and lightweight
- precise temperature control
- quiet operation



MODEL	input voltage max (V)	input current max (A)	output Q _{max} ¹		output ΔT _{max} ²	
			T _h =27°C (W)	T _h =50°C (W)	T _h =27°C (°C)	T _h =50°C (°C)
CP60140	2.1	6	7.1	7.9	68	75
CP60133	3.8	6	12.2	13.6	66	72
CP60240	3.8	6	13.0	14.5	68	75
CP60233	8.6	6	27.9	31.2	66	72
CP60340	8.6	6	29.0	32.4	68	75
CP60333	15.4	6	50.5	56.5	66	72
CP60440	15.4	6	53.0	59.3	68	75



Notes: 1. maximum cooling capacity at I_{max}, V_{max} and ΔT=0°C
 2. maximum temperature difference at I_{max}, V_{max} and Q=0W (maximum parameters are measured in a vacuum)



PART NUMBER KEY

GENERAL



parameter	conditions/description	min	typ	max	units
internal resistance ³	CP60140	0.261	0.290	0.319	Ω
	CP60133	0.45	0.50	0.55	Ω
	CP60240	0.477	0.530	0.583	Ω
	CP60233	1.08	1.2	1.32	Ω
	CP60340	1.089	1.210	1.331	Ω
	CP60333	1.98	2.2	2.42	Ω
	CP60440	1.953	2.170	2.387	Ω
solder melting temperature	connection between thermoelectric pairs			138	°C
assembly compression				98.07	N/cm ²
				10	kgf/cm ²
hot side plate				80	°C
MTBF				200,000	hours



Notes: 3. measured by AC 4-terminal method at 25°C



For further information and product selection refer to peltier application notes.pdf



CP60140 PERFORMANCE (Th=27°C)**CP60140 PERFORMANCE (Th=50°C)**



CP60133 PERFORMANCE (Th=27°C)**CP60133 PERFORMANCE (Th=50°C)**

CP60240 PERFORMANCE (Th=27°C)**CP60240 PERFORMANCE (Th=50°C)**

CP60233 PERFORMANCE (Th=27°C)**CP60233 PERFORMANCE (Th=50°C)**


CP60340 PERFORMANCE (Th=27°C)**CP60340 PERFORMANCE (Th=50°C)**

CP60333 PERFORMANCE (Th=27°C)**CP60333 PERFORMANCE (Th=50°C)**



CP60440 PERFORMANCE (T_h=27°C)**CP60440 PERFORMANCE (T_h=50°C)**

MECHANICAL DRAWING

units: mm



	MATERIAL	PLATING
ceramic plate	Al ₂ O ₃ (Alumina)	
sealer	silicon rubber RTV	
lead wire (3.3 mm thick)	UL1430 (22AWG)	tin
lead wire (4.0 mm thick)	UL1674 (20AWG)	tin
joint cover	silicon rubber RTV	



MODEL	LENGTH x WIDTH (mm)	THICKNESS (mm)
CP60140	15 x 15 ± 0.3	4.0 ± 0.1
CP60133	15 x 15 ± 0.3	3.3 ± 0.1
CP60240	20 x 20 ± 0.3	4.0 ± 0.1
CP60233	20 x 20 ± 0.3	3.3 ± 0.1
CP60340	30 x 30 ± 0.3	4.0 ± 0.1
CP60333	30 x 30 ± 0.3	3.3 ± 0.1
CP60440	40 x 40 ± 0.3	4.0 ± 0.1

REVISION HISTORY

rev.	description	date
1.0	initial release	09/03/2009
1.01	applied new template	05/08/2012

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

CUI Inc.:

[CP60440](#) [CP60333](#) [CP60133](#) [CP60240](#) [CP60233](#)