


CPL, CPLA, and CPLE

Multi-phase power inductors



Product description

- High current multi-phase inductor applications
- 50nH per phase coupled inductor
- CPLA Family features acoustic noise dampening properties
- CPLE Family features optimized core material for enhanced light load efficiency
- Ferrite core material
- Frequency range up to 2MHz
- Patents pending
- Halogen free, lead free and RoHS compliant

Applications

- For exclusive use with Volterra® or Maxim® VPR-Devices

Environmental Data

- Storage temperature range (component): -40°C to +125°C
- Operating temperature range: -40°C to +125°C (ambient plus self-temperature rise)
- Solder reflow temperature: J-STD-020D compliant



Volterra® is a registered trademark of Volterra Semiconductor, LLC.

Maxim® is a registered trademark of Maxim Integrated Devices, Inc.

Product Specifications

Function Specifications						Test Specifications				
Part Number ^{4,5}	Inductor phases	DCR (Ω) Nom. @25°C	DCR (Ω) Max. @25°C	Rated Inductance per Phase ³ (nH)	I Rated per Phase ³ (ADC)	Pin numbers	OCL ^{1,2} (nH)	Pin numbers	OCL ^{1,2} (nH)	Magnetizing Inductance ² (nH) @ 5ADC (25°C)
CPL Family—Standard										
CPL-2-50TR-R	2	0.0005	0.0006	50 ± 20%	40	(1-2)	365 ±18%	(3-4)	365 ±18%	300
CPL-3-50TR-R	3	0.0005	0.0006	50 ± 20%	40	(3-4)	490 ±20%	(1-2), (5-6)	365 ±18%	400
CPL-4-50TR-R	4	0.0005	0.0006	50 ± 20%	40	(3-4), (5-6)	490 ±20%	(1-2), (7-8)	365 ±18%	400
CPL-5-50TR-R	5	0.0005	0.0006	50 ± 20%	40	(3-4), (5-6), (7-8)	490 ±20%	(1-2), (9-10)	365 ±18%	400
CPL-6-50TR-R	6	0.0005	0.0006	50 ± 20%	40	(3-4), (5-6), (7-8), (9-10)	490 ±20%	(1-2), (11-12)	365 ±18%	400
CPLA Family—Acoustic Noise Dampening										
CPLA-2-50TR-R	2	0.0005	0.0006	50 ± 20%	40	(1-2)	365 ±18%	(3-4)	365 ±18%	300
CPLA-3-50TR-R	3	0.0005	0.0006	50 ± 20%	40	(3-4)	490 ±20%	(1-2), (5-6)	365 ±18%	400
CPLA-4-50TR-R	4	0.0005	0.0006	50 ± 20%	40	(3-4), (5-6)	490 ±20%	(1-2), (7-8)	365 ±18%	400
CPLA-5-50TR-R	5	0.0005	0.0006	50 ± 20%	40	(3-4), (5-6), (7-8)	490 ±20%	(1-2), (9-10)	365 ±18%	400
CPLE Family—Low Core Loss for Light Load Efficiency										
CPLE-2-50TR-R	2	0.0005	0.0006	50 ± 20%	40	(1-2)	365 ±18%	(3-4)	365 ±18%	300
CPLE-3-50TR-R	3	0.0005	0.0006	50 ± 20%	40	(3-4)	490 ±20%	(1-2), (5-6)	365 ±18%	400
CPLE-4-50TR-R	4	0.0005	0.0006	50 ± 20%	40	(3-4), (5-6)	490 ±20%	(1-2), (7-8)	365 ±18%	400
CPLE-5-50TR-R	5	0.0005	0.0006	50 ± 20%	40	(3-4), (5-6), (7-8)	490 ±20%	(1-2), (9-10)	365 ±18%	400

1. OCL (Open Circuit Inductance)

2. Test parameters: 1MHz, 0.1Vrms, 0.0Adc. @25°C


3. The rated current and rated inductance per phase is determined by Volterra's testing and circuit design. Additional information can be provided by contacting Volterra.

4. Part Number Definition: CPLx-y-50TR-R-50TR-R

- CPLx= Product code and size - CPL (standard)/CPLA (acoustic dampening)/CPLE (low core loss)
- -y= number of phases • -50 = rated inductance value per phase in nH
- TR= Tape and reel • -R suffix= RoHS compliant


5. This device is licensed for use only when incorporated within a voltage regulator employing power regulating devices manufactured by Volterra Semiconductor, LLC or Maxim Integrated Devices, Inc. No license is granted expressly or by implication to use this device with power regulating devices manufactured by any company other than Volterra or Maxim.

Dimensions (mm)




Pad layouts & schematics (mm)

Tolerances are $\pm 0.2\text{mm}$ unless otherwise specified.



Packaging Information (mm)

Supplied in tape-and-reel packaging, 750 parts per reel, 13" diameter reel.



Solder reflow profile




Table 1 - Standard SnPb Solder (T_C)

Package Thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5mm)	235°C	220°C
≥2.5mm	220°C	220°C

Table 2 - Lead (Pb) Free Solder (T_C)

Package Thickness	Volume mm ³ <350	Volume mm ³ 350 - 2000	Volume mm ³ >2000
<1.6mm	260°C	260°C	260°C
1.6 – 2.5mm	260°C	250°C	245°C
>2.5mm	250°C	245°C	245°C

Reference JEDEC J-STD-020D

Profile Feature	Standard SnPb Solder	Lead (Pb) Free Solder
Preheat and Soak		
• Temperature min. (T_{smin})	100°C	150°C
• Temperature max. (T_{smax})	150°C	200°C
• Time (T_{smin} to T_{smax}) (t_s)	60-120 Seconds	60-120 Seconds
Average ramp up rate T_{smax} to T_P	3°C/ Second Max.	3°C/ Second Max.
Liquidous temperature (T_L)	183°C	217°C
Time at liquidous (t_L)	60-150 Seconds	60-150 Seconds
Peak package body temperature (T_P)*	Table 1	Table 2
Time (t_P)** within 5 °C of the specified classification temperature (T_C)	20 Seconds**	30 Seconds**
Average ramp-down rate (T_P to T_{smax})	6°C/ Second Max.	6°C/ Second Max.
Time 25°C to Peak Temperature	6 Minutes Max.	8 Minutes Max.

* Tolerance for peak profile temperature (T_P) is defined as a supplier minimum and a user maximum.

** Tolerance for time at peak profile temperature (t_P) is defined as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
www.eaton.com/elx

© 2015 Eaton
All Rights Reserved
Printed in USA
Publication No. 4362 BU-SB12070
December 2015

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Eaton:

[CPLE-5-50TR-R](#) [CPLE-3-50TR-R](#) [CPLE-2-50TR-R](#) [CPLE-4-50TR-R](#)