


# AT-CUT CRYSTAL UNIT (SMD • Ceramic Package)

## CS325


3000pcs/reel




### FEATURES

- High-density SMD type.
- Reliable ceramic package and excellent environmental characteristics.
- Suitable for various applications such as communication devices, AV devices and other equipment.
- Complete Pb free product.

### DIMENSION [mm]



### SOLDER PAD LAYOUT [mm]



### STANDARD SPECIFICATIONS

Item	Model	CS325	Conditions
Nominal Frequency	$f_0$	12.0MHz~54.0MHz (Fundamental)	Need to contact us for the available frequency
Frequency Tolerance	$\Delta f/f_0$	$\pm 30$ ppm	at 25°C
Frequency Tolerance over Operating Temperature Range	$\Delta f/f_0$	$\pm 30$ ppm	-10°C ~ +60°C
Operating Temperature Range	$T_{OPR}$	-40°C ~ +85°C	
Storage Temperature Range	$T_{STR}$	-55°C ~ +125°C	
Motional (series) resistance	$R_1$	Refer to the following table	at 25°C
Load capacitance	$C_L$	16.0pF, 18.0pF	Need to specify your requirement
Shunt capacitance	$C_0$	5.0pF Max.	
Level of drive	$D_L$	10 $\mu$ W (100 $\mu$ W Max.)	
Insulation Resistance	$I_R$	500M $\Omega$ Min.	DC100V $\pm$ 15V
Aging (first year)	$\Delta f/f_0$	$\pm 5$ ppm Max.	25°C $\pm$ 3°C

### MOTIONAL (SERIES) RESISTANCE ( $R_1$ )

Frequency Range	12.0MHz $\leq f_0 < 16.0$ MHz	16.0MHz $\leq f_0 < 20.0$ MHz	20.0MHz $\leq f_0 < 30.0$ MHz	30.0MHz $\leq f_0 < 54.0$ MHz
ESR	150 $\Omega$ Max.	120 $\Omega$ Max.	80 $\Omega$ Max.	50 $\Omega$ Max.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Citizen:

[CS325-40.000MABJ-UT](#) [CS325-44.000MABJ-UT](#) [CS325-48.000MABJ-UT](#) [CS325-53.125MABJ-UT](#) [CS325-33.3333MABJ-UT](#) [CS325-33.000MABJ-UT](#) [CS325-13.560MABJ-UT](#) [CS325-16.000MABJ-UT](#) [CS325-16.384MABJ-UT](#) [CS325-26.000MABJ-UT](#) [CS325-30.000MABJ-UT](#) [CS325-18.432MABJ-UT](#) [CS325-32.000MABJ-UT](#) [CS325-27.000MABJ-UT](#) [CS325-28.6363MABJ-UT](#) [CS325-25.000MABJ-UT](#) [CS325-24.576MABJ-UT](#) [CS325-24.000MABJ-UT](#) [CS325-19.200MABJ-UT](#) [CS325-13.000MABJ-UT](#) [CS325-14.31818MABJ-UT](#) [CS325-12.000MABJ-UT](#) [CS325-27.120MABJ-UT](#)