Covert Dual Band Antenna (Patented)

GSM/CDMA Bands and WiFi 2.4 GHz



CVS Series Dual Band Strip Covert Antennas

These antennas are designed for covert use in/on a vehicle, or for any type of embedded/surface application. Additional applications would be ATM machines, remote credit card processing, wireless kiosks, and telemetry radios, perhaps in NEMA boxes. These antennas operate on dual band configurations and can be used for cell phones or GSM/EV-DO/GPRS/1xRTT modem applications. Models are also available for Nextel modems and ISM 915 MHz modems. A single band model is available for 2.4 GHz WiFi (802.11 b/g)

These antennas are compact, yet provide 2.5 dBi gain performance. The antennas are ground plane independent and can be mounted in a variety of locations. They can be installed behind rearview mirrors, under a dashboard or rear window deck/shelf. Since they are thin. they can also fit into the molding of vehicles, surface or subsurface mount in various electronic equipment.

The CVS antennas are weather resistant. These antennas are provided with double sided tape and a mounting clip for standard installation applications. They can be installed without the mounting clip by simply using the double sided tape.

- Halfwave 2.5 dBi gain styles
- Low profile & compact; perfect for Covert use or unobstructed view use.
- Weather resistant design for inside/outside applications
- Models for popular dual band operation; GSM, CDMA, GPRS, Nextel, ISM & WiFi

When mounting the antenna, care should be taken to ensure the antenna is positioned so that no metal or metallized finish obstructs the radiation pattern of the antenna.

The CVS series is housed within a black ABS rugged radome and is provided with 8 ft of RG-174 cable (2.5 meters). Models are typically outfitted with Male TNC or SMA connectors. Other connectors are available upon request. This model is also available with an integral GPS antenna in a slightly larger package.

Model Numbers

Hz GPRS
PRS
Hz DCS

Specify desired connector at time of order (SMA or TNC). Special configurations available upon request. Please consult factory for details/availability.

Specifications

Frequency:

US 850 GSM/CDMA 824-894 MHz Nextel 806-870 MHz US 1.9 GSM/CDMA 1850-1990 MHz 1.9 GPRS/1xRTT 1850-1990 MHz EU 900 GSM (& ISM) 870-960 MHz EU GSM @1800 1710-1880 MHz WiFi/802.11 b/g 2400-2485 MHz Gain:

Bandwidth@2:1 VSWR: Impedance:

Maximum Power:

2.5 dBi max

See freq range above 50 Ohm nominal

10 Watts

Operating Temp: -40° to +80° C

CVS Series Dimension: 3.75"L x 1 1/4"W x 3/8"D

95 mm x 32mm x 9 mm

Cable:

CVS Series: 8 ft RG-174 (2.5 meters) **Connectors:** TNC or SMA, others available, consult factory

CVS Material: ABS plastic, black Mounting: Slide-in clip, or direct double sided tape

Special configurations available, please consult factory

for details.