

User's Guide

D0111LT-33-1101

VFD

(Vacuum Fluorescent Display Character Module)

For product support, contact

Newhaven Display International
2511 Technology Drive #101
Elgin, IL 60124
Tel: (847) 844-8795 Fax: (847) 844-8796

October 31, 2006

Vacuum Fluorescent Display Specification

PART NUMBER: **D0111LT-33-1101**

FEATURES: 11 Digits, 7-Segmented, Instrumentation, Scales

APPLICATION: Character Display (7-Segmented)

RATINGS: Below


Outer Dimensions	Panel Length	P.L.	160.0	mm	
	Panel Height	P.H.	33.0	mm	
	Panel Thickness	P.T.	8.0	mm	
Leads	Lead Pitch	L.P.	4.0	mm	
	Lead Out	-	SIL		
Character Size	Character Height	C.H.	12.5	mm	
	Character Width	C.W.	6.3	mm	
Item	Symbol	Min.	Recommended	Max.	Unit
Filament Voltage	Ef	5.5	6.1	6.7	Vac
Peak Grid Voltage	ec	-	28.0	36.0	Vp-p
Peak Anode Voltage	eb	-	28.0	36.0	Vp-p
Life	tp	10,000	-	-	Hrs
Duty Cycle	Du	-	1/12.5	-	-
Pulse Width	tp	-	80	-	uS
Operating Temperature	Topr	-40	-	+ 85	C
Storage Temperature	Tstg	-50	-	+ 95	C
Color of Illumination	Green				

D0111LT-33-1101

Electrical Characteristics

Item	Symbol	Test Condition	Min.	Typical	Max.	Unit
Filament Current	I _f -	E _f = 6.1 V _{dc} e _b = e _c = 0	117.0 -	130.0 -	143.0 -	mA _{dc} -
Anode Current	i _b /1G~11G - - - - -	E _f = 6.1 V _{ac} e _b = 28.0 V _{p-p} e _c = 28.0 V _{p-p} D _u = 1/12.5 t _p = 80 uS All Segments Lit	- - - - -	8.0 - - - -	17.0 - - - -	mA _{p-p} mA _{p-p} mA _{p-p} mA _{p-p} mA _{p-p}
Grid Current	i _c / 1G~11G - - - -		- - - - -	11.0 - - - -	18.1 - - - -	MA _{p-p} MA _{p-p} MA _{p-p} MA _{p-p} MA _{p-p}
Luminance	L(G) -		343 (100)	686 (200)	- 	cd/m ² fL
Luminance Ratio	L _{min} /L _{max}		50	-	-	%
Grid Cut-off Voltage	E _{cco}	E _f = 6.1 V _{dc} e _b = 28.0 V _{dc} All Segments Lit	-7.0	-	-	V _{dc}
Anode Cut-off Voltage	E _{bco}	E _f = 6.1 V _{ac} e _c = 28.0 V _{p-p} D _u = 1/12.5 t _p = 80uS	-7.0	-	-	V _{dc}

OUTLINE DRAWING (UNIT :mm)




TERMINAL CONNECTION

TERMINAL NO	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33
ELECTRODE	F	NC	11G	NC	P7	10G	P6	P5	9G	P4	P9	8G	P10	P14	7G	P13	P12	6G	5G	P11	P8	4G	P3	P2	3G	NC	P1	2G	P16	P15	1G	NC	F

Notes:

- F: Filament
- G: Grid
- NC: Connection
- P: Anode



ANODE CONNECTION

	11G	10G	9G	8G	7G	6G	5G	4G	3G	2G	1G
P1	a	a	a	a	a	a	a	a	a	a	a
P2	b	b	b	b	b	b	b	b	b	b	b
P3	c	c	c	c	c	c	c	c	c	c	c
P4	d	d	d	d	d	d	d	d	d	d	d
P5	e	e	e	e	e	e	e	e	e	e	e
P6	f	f	f	f	f	f	f	f	f	f	f
P7	g	g	g	g	g	g	g	g	g	g	-
P8	Dp	Dp	Dp	Dp	Dp	Dp	Dp	Dp	Dp	Dp	Dp
P9	com	com	com	com	com	com	com	com	com	com	com
P10	-	▽	▽	-	▽	▽	-	▽	▽	-	▽
P11	-	-	-	-	-	-	-	-	-	▽	-
P12	-	-	-	-	-	-	▽	-	-	-	-
P13	-	-	-	▽	-	-	-	-	-	-	-
P14	▽	-	-	-	-	-	-	-	-	-	-
P15	-	-	-	-	-	-	-	-	-	-	g
P16	-	-	-	-	-	-	-	-	-	-	g

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Newhaven Display:

D0111LT-33-1101