

DFJ Class J high speed fuses



Catalog symbol:

- DFJ_-

Description:

The Bussmann™ series DFJ drive fuse is a high speed, current-limiting fuse that provides maximum protection for AC and DC drives and controllers and meet NEC® branch circuit protection requirements. The drive fuse has the lowest I^2t of any branch circuit fuse to protect power semiconductor devices that utilize diodes, GTOs, SCRs and SSRs.

Specifications:

Ratings

- Volts
 - 600Vac (or less)
 - 450Vdc (or less, 15-600A)
- Amps 1-600A
- IR
 - 200kA RMS Sym.
 - 100kA DC

Agency information

- UL® Listed Standard 248-8, Class J, Guide JDDZ, File E4273
- CSA® Certified, C22.2 No. 248.8, Class 1422-02, File 53787
- RoHS compliant
- CE

Features:

- Easily coordinated with existing and new variable speed drives and electric controllers.
- Standard Class J dimensions allow using readily available fuse blocks, holders and switches.
- Has the lowest let-through energy of any branch circuit overcurrent protective device.

Typical applications

- Protection of AC and DC drives
- Equipment using power semiconductor devices

Catalog numbers (amps):

DFJ-1	DFJ-15	DFJ-60	DFJ-200
DFJ-2	DFJ-17.5	DFJ-70	DFJ-225
DFJ-3	DFJ-20	DFJ-80	DFJ-250
DFJ-4	DFJ-25	DFJ-90	DFJ-300
DFJ-5	DFJ-30	DFJ-100	DFJ-350
DFJ-6	DFJ-35	DFJ-110	DFJ-400
DFJ-8	DFJ-40	DFJ-125	DFJ-450
DFJ-10	DFJ-45	DFJ-150	DFJ-500
DFJ-12	DFJ-50	DFJ-175	DFJ-600

Carton quantity:

Amp rating	Carton qty.
1-60	10
70-200	5
225-600	1

Electrical characteristics:


Catalog number	Amps	I ² t (A ² Sec) @ 600Vac/100kA	Watts loss
		Pre-arc	Clearing
DFJ-15	15	4	4.1
DFJ-20	20	8	4.0
DFJ-25	25	12	4.9
DFJ-30	30	20	5.5
DFJ-35	35	55	6.8
DFJ-40	40	90	8.6
DFJ-50	50	140	8.7
DFJ-60	60	290	8.5
DFJ-70	70	450	12
DFJ-80	80	650	13
DFJ-90	90	1010	13
DFJ-100	100	1460	13
DFJ-110	110	1710	17
DFJ-125	125	3580	15
DFJ-150	150	5080	19
DFJ-175	175	6310	23
DFJ-200	200	9850	24
DFJ-225	225	11,420	29
DFJ-250	250	17,000	30
DFJ-300	300	23,500	36
DFJ-350	350	38,800	39
DFJ-400	400	62,200	40
DFJ-450	450	44,600	56
DFJ-500	500	79,500	52
DFJ-600	600	138,000	57

Recommended fuse blocks and holders:


Fuse amps	1-Pole	2-Pole	3-Pole
"Pyramid" blocks (data sheet No. 1108)			
up to 30	—	—	JP60030-3
CH holders (data sheet No. 2144)			
up to 30	CH30J1	CH30J2	CH30J3
35-60	CH60J1	CH60J2	CH60J3
Safety J™ holders (data sheet No. 1152)			
up to 30	JT60030	—	—
35-60	JT60060	—	—
JM modular fuse blocks (data sheet No. 3192 and 10289)			
up to 30	JM60030-1	JM60030-2	JM60030-2
35-60	JM60060-1CR	JM60060-2CR	JM60060-3CR
70-100	JM60100-1CR	JM60100-2CR	JM60100-3CR
110-200	JM60200-1CR	JM60200-2CR	JM60200-3CR
225-400	JM60400-1CR	JM60400-2CR	JM60400-3CR
450-600	JM60600-1CR	JM60600-2CR	JM60100-3CR
JM power distribution fuse blocks (data sheet No. 10192)			
up to 30	JM60030-1MW	JM60030-2MW	JM60030-3MW
35-60	JM60060-1MW	JM60060-2MW	JM60060-3MW
70-100	JM60100-1MW14	JM60100-2MW14	JM60100-3MW14
110-200	JM60200-1MW16	JM60200-2MW16	JM60200-3MW16
225-400	JM60400-1MW16	JM60400-2MW16	JM60400-3MW16
	JM60400-1MW26*	JM60400-2MW26*	JM60400-3MW26*

* Lineside dual box lug terminal.


Dimensions - in:




1A to 30A




35A to 60A




70A to 100A



110A to 200A




225A to 400A




450A to 600A

Time-current curves — average melt



Current-limitation curves



The only controlled copy of this data sheet is the electronic read-only version located on the Eaton network drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Eaton
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com

Bussmann Division
114 Old State Road
Ellisville, MO 63021
United States
Eaton.com/bussmannseries

Eaton, Bussmann and Low-Peak are valuable trademarks of Eaton in the US and other countries. You are not permitted to use the Eaton trademarks without prior written consent of Eaton.

CSA is a registered trademark of the Canadian Standards Group.
NEC is a registered trademark of the National Fire Protection Association, Inc.
UL is a registered trademark of the Underwriters Laboratories, Inc.

For Eaton's Bussmann series product information,
call 1-855-287-7626 or visit:
Eaton.com/bussmannseries

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Cooper Bussmann:

[DFJ-1](#) [DFJ-10](#) [DFJ-100](#) [DFJ-110](#) [DFJ-12](#) [DFJ-125](#) [DFJ-15](#) [DFJ-150](#) [DFJ-175](#) [DFJ-17.5](#) [DFJ-2](#) [DFJ-20](#) [DFJ-200](#) [DFJ-225](#) [DFJ-25](#) [DFJ-250](#) [DFJ-3](#) [DFJ-30](#) [DFJ-300](#) [DFJ-35](#) [DFJ-350](#) [DFJ-4](#) [DFJ-400](#) [DFJ-45](#) [DFJ-450](#) [DFJ-5](#) [DFJ-50](#) [DFJ-500](#) [DFJ-6](#) [DFJ-60](#) [DFJ-600](#) [DFJ-70](#) [DFJ-8](#) [DFJ-80](#) [DFJ-90](#)

Eaton:

[DFJ-40](#)