



Search Results

- Evaluate
- FAQ's
- Design a Solution
- Part Drawings
 - PDFMetric Femal ..
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips Within Results

Text Search: 'DMNF663FIB-2K'

Your search criteria matched only one product, shown below

DMNF6-63FIB-2K



Standard nylon provides an insulation support for normal requirements. The fully Insulated design gives excellent flashover protection and the funnel entry speeds wire insertion for increased productivity.

- Continuously molded design provides reliable, consistent performance through the applicator for a high quality termination every time
- Disconnect can be inserted and removed from the male tab without the use of tools for lower installed cost
- Fully insulated design provides protection from electrical shorts
- Disconnects available in common industry tab sizes
- Internal wire stop assures proper length of insertion into terminal barrel, providing a higher quality connection

	Part Number	DMNF663FIB-2K
	RoHS Compliancy Status	Compliant
	Part Description	Metric reel-fed female disconnect, 4.0 - 6.0mm ² wire range, 6.3mm x .8mm tab size, nylon fully insulated, funnel entry.
	Product Type	Disconnects – Metric ReelFed
	CSA Certified	Yes
	UL Listed	Yes
	Height (mm)	5.8
	Length (mm)	24.4
	Width (mm)	8.9
	CA-800 Series Crimp Die	CD-800-13
	CA9 Series Crimp Die	CD9-13B
	Max. Ins.	5.6
	Panduit Color Code	Yellow
	Pieces Per Reel	2000
	Pricing Description	Metric Female Disconnect, nylon fully insulated, 4.0 6.0mm ² wire range, 6.3 x .8mm tab size, funnel entry
	Tab Size (mm)	6.3 x .8
	Wire Range (mm ²)	4.0 – 6.0
	Min. Order UOM	PC
	Min. Order Qty.	2000
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.