

DOL-1204-G10MRN

Plug connectors and cables

ACCESSORIES





Ordering information

Туре	Part no.
DOL-1204-G10MRN	6058478

Other models and accessories

www.sick.com/Plug_connectors_and_cables

Detailed technical data

Technical specifications

Accessory group Accessory family Connection type head A Female connector, M12, 4-pin, straight Connection type head B Connection type Open conductor heads Connector material PP Connector color Locking nut material On m, 4-wire Jacket color Gray
Connection type head A Connection type head B Connection type Open conductor heads Connector material PP Connector color Gray Locking nut material Open conductor heads Stainless steel (V4A/1.4404) Cable 10 m, 4-wire PP Jacket material PP Gray Gray
Connection type head B Connection type Open conductor heads Connector material PP Connector color Connector color Coking nut material Stainless steel (V4A/1.4404) Cable In m, 4-wire PP In material PP In m, 4-wire PP
Connection type Connector material PP Connector color Connector color Connector material Connector color Connector color Stainless steel (V4A/1.4404) Cable 10 m, 4-wire PP Jacket material PP Gray Gray Gray
Connector material PP Connector color Gray Locking nut material Stainless steel (V4A/1.4404) Cable 10 m, 4-wire Jacket material PP Gray Gray Gray Gray
Connector color Locking nut material Stainless steel (V4A/1.4404) Cable 10 m, 4-wire Pp 1) Jacket material Pr 1) Gray
Locking nut material Stainless steel (V4A/1.4404) 10 m, 4-wire PP 1) Jacket material Pr 2) Gray
Cable 10 m, 4-wire PP 1) Jacket color Gray
Jacket material PP 1) Jacket color Gray
Jacket color Gray
Cable diameter 4.6 mm
Conductor cross-section 0.34 mm ²
Shielding Unshielded
Bending radius > 5 x cable diameter (stationary position), > 10 x cable diameter (flexible use)
Bending cycles ≥ 4,000,000
Tightening torque 1 Nm
Reference voltage ≤ 250 V
Rated impulse voltage 2.5 kV
Current loading 4 A
Special feature Drag chain use
Application Hygienic systems
Note This product is generally resistant to chemical cleaning agents (see ECOLAB) and other chemical compounds such as H2O2 and CH2O2. Before permanent installation is carried out, the material's resistance to the cleaning agent being used must be checked. 2)
Authorizations Ecolab
Ambient operating temperature -40 °C +105 °C, stationary position -25 °C +105 °C, flexible use

 $^{^{1)}}$ Silicone-free, halogen-free, LABS-free.

²⁾ Tested detergent: P3-topactive DES, P3-topactive 200, P3-topax 52, P3-topax 66 und P3-topax 91.


Enclosure rating	IP 67
	IP 69K

 $^{^{1)}}$ Silicone-free, halogen-free, LABS-free.

Classifications

ECI@ss 5.0	19030312
ECI@ss 5.1.4	19030312
ECI@ss 6.0	27060304
ECI@ss 6.2	27060304
ECI@ss 7.0	27060304
ECI@ss 8.0	27060304
ECI@ss 8.1	27060304
ECI@ss 9.0	27060304
ETIM 5.0	EC000830
ETIM 6.0	EC000830
UNSPSC 16.0901	26121604

Dimensional drawing (Dimensions in mm (inch))



²⁾ Tested detergent: P3-topactive DES, P3-topactive 200, P3-topax 52, P3-topax 66 und P3-topax 91.

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

