

Search Results

- Evaluate
- FAQ's
 - Selection Guides
 - PDFConvenience..
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips

Text Search: 'DV18-250P-E'

Your search criteria matched only one product, shown below

DV18-250P-E



- Disconnect can be inserted and removed from the male tab without the use of tools for lower installed cost
- Combination of female disconnect and male tab allows versatility in points of connection
- Multiple connection points allow additional circuits to be added to existing equipment without expensive rework
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
- UL Flammability UL 94V -2/HB, maximum insulation temperature 194°F (90°C)
- Rated up to 300 V

Part Number	DV18-250P-E
RoHS Compliancy Status	Compliant
Part Description	Piggyback Disconnect, vinyl barrel insulated, 22– 18 AWG, .250 x .032 tab size.
Product Type	Terminals
CSA Certified	No
UL Listed	No
Length (In.)	0.88
Length (mm)	22.4
Width (In.)	0.29
Width (mm)	7.4
CE Compliant	No
Insulation	Vinyl
Max. Ins.	0.130
Max. Ins. (mm)	3.3
Panduit Color Code	Red
Plating Type	Tinned
Pricing Description	Terminal Convenience Package
Tab Size (In.)	0.250 x 0.032
Tab Size (mm)	6.3 x 0.8
Temperature Rating	194 Degrees Fahrenheit (90 Degrees Celsius)
Tool	CT-100A, CT-260, CT-1550, CT-1551, CT-2500
Wire Range	22 – 18 AWG
Wire Range (mm ²)	0.5 – 1.0
Min. Order UOM	PC
Min. Order Qty.	20
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	<input type="button" value="e"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.