






REVISION RECORD		
REV	DESCRIPTION	DRFT



PIN NO.	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
SIGNAL NAME	GND	SSTXp1	SSTXn1	VBUS	CC1	Dp1	Dn1	SBU1	VBUS	SSRXn2	SSRXp2	GND
PIN NO.	B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1
SIGNAL NAME	GND	SSRXp1	SSRXn1	VBUS	SBU2	Dn1	Dp1	CC2	VBUS	SSTXn2	SSTXp2	GND

NOTES:

ELECTRICAL CHARACTERISTICS:

1. LOW LEVEL CONTACT RESISTANCE: INITIAL $40m\Omega$ FOR ALL CONTACT MAX. AFTER $10m\Omega$ MAX. CHANGE.
2. DIELECTRIC WITHSTANDING VOLTAGE: 100 VAC FOR 1 MINUTE SEA LEVEL.
3. INSULATION RESISTANCE: $100M\Omega$ MIN.
4. CURRENT RATING: VBUS AND GND CONTACTS RATED AT 1.25A EA, PARALLELED FOR A TOTAL OF 5A.


MECHANICAL CHARACTERISTICS:

1. INSERTION FORCE: 20N MAX
2. EXTRACTION FORCE: DURABILITY 1~1000 CYCLES 8N MIN. 20N MAX. DURABILITY 1001~10000 CYCLES 6N MIN. 20N MAX.
3. DURABILITY: 10,000 CYCLES
4. PLATING OF CONTACT: Au 30μ PLATING ON CONTACT AREA.
5. OPERATING TEMPERATURE: -40°C TO $+85^\circ\text{C}$

DETACHED LISTS	MM (INCH)		TOLERANCES EXCEPT AS NOTED	RoHS Compliant	TITLE
	MM	INCH			
	.0 ± 0.25	±			USB TYPE- C FULL FEATURE CONN.
	.00 ± 0.20	±			RECEPTACLE - MID MOUNT TYPE
	.000 ± 0.10	±			
	ANGLES ± 1°			DF TO : LYNN	DRAWING NO. CE8124-011-01
				DATE : 06/23/2015	/PART NO. E8124-011-01
				SCALE : 1:1	SIZE A3 REV 0
				DO NOT SCALE DRAWING	SHEET 1 OF 2

 Pulse
Electronics

REVISION RECORD		
REV	DESCRIPTION	DRFT



RECOMMENDED PCB LAYOUT
THICKNESS IS 0.9mm
TOLERANCE ± 0.05

DETACHED LISTS	MM (INCH)		TOLERANCES EXCEPT AS NOTED	RoHS Compliant	TITLE
	MM	INCH			
	.0 ± 0.25	\pm			USB TYPE-C FULL FEATURE CONN.
	.00 ± 0.20	\pm			RECEPTACLE - MID MOUNT TYPE
	.000 ± 0.10	\pm			
ANGLES $\pm 1^\circ$	DF TD	LYNN	DRAWING NO.	CE8124-011-01	SIZE
	DATE	06/23/2015	/PART NO.	E8124-011-01	REV
THIRD ANGLE PROJECTION	SCALE	1:1	DO NOT SCALE DRAWING	SHEET 2 OF 2	A3 0

 Pulse
Electronics

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pulse:

[E8124-011-01](#)