


Stacked Coin Type

Series: **SE****■ Features**

- Endurance : 70 °C 1000 h
- -40 °C guarantee
- Automatic insertion available
- RoHS directive compliant

**■ Recommended Applications**

- Memory back-up for video and audio equipment, cameras, telephones, printers, data terminals, rice cookers and intelligent remote controls.

■ Specifications

Category	Temp. Range	-40 °C to +70 °C	
Maximum Operating Voltage	5.5 V.DC		
Nominal Cap. Range	0.22 F		
Characteristics at Low Temperature	Capacitance change	±30 % of initial measured value at +20 °C (at -40 °C)	
	Internal resistance	≤7 times of initial measured value at +20 °C (at -40 °C)	
Endurance	After 1000 hours application of 5.5 V. DC at +70 °C, the capacitor shall meet the following limits.		
	Capacitance change	±30 % of initial measured value	
	Internal resistance	≤4 times of initial specified value	
Shelf Life	After 1000 hours storage at +70 °C without load, the capacitor shall meet the specified limits for Endurance.		

■ Dimensions in mm(not to scale)

(Unit : mm)

Dimensions	Nominal	Tolerance
ϕd	0.55	±0.05
P ₀	12.7	±0.2
F	5.0	+0.8 -0.2
W	18.0	±0.5
W ₀	5.5≤	—
W ₁	9.0	±0.5
W ₂	0 to 3.0	—
H ₀	16.4	±0.5
ϕD_0	4.0	±0.2
P	12.7	±1.0
P ₁	3.85	±0.50
P ₂	6.35	±1.00
$\Delta h, \Delta h_1$	0	±1.0
H ₁	30.3≥	—

■ Standard Products

Maximum Operating Voltage (V.DC)	Capacitance (F)	Capacitance tolerance (F)	Internal resistance (Initial specified value) (Ω) at 1kHz	Recommended discharge current (μA)	Part number	Mass (Reference value) (g)	Min. Packaging Q'ty (pcs)
5.5	0.22	0.176 to 0.396	≤ 75	300 or less	EECSE0H224N	1.0	1000

Note: 1. When ordering please observe the minimum packaging quantity.

2. When the surface mount component goes through UV or a heat oven to affix the adhesive glue, the capacitor's surface temperature should not exceed 100 °C for more than 60 seconds (maximum temperature should not exceed 105 °C)

3. Do not use reflow soldering. (IR, Atmosphere heating methods, etc.)
Please refer to the page of "Application Guidelines".

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Panasonic:](#)

[EEC-SE0H224N](#)