

## HIGH EFFICIENCY RECTIFIERS

**VOLTAGE RANGE: 50 --- 400 V**  
**CURRENT: 1.0 A**


### FEATURES

- ◇ Low cost
- ◇ Diffused junction
- ◇ Low leakage
- ◇ Low forward voltage
- ◇ High current capability
- ◇ Easily cleaned with alcohol, Isopropanol and similar solvents
- ◇ The plastic material carries U/L recognition 94V-0

### MECHANICAL DATA

- ◇ Case: JEDEC DO-41, molded plastic
- ◇ Terminals: Axial lead, solderable per MIL-STD-750, Method 2026
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.012 ounces, 0.34 grams
- ◇ Mounting position: Any

### DO - 41



### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.



|                                                                                                                |                    | EGP<br>10A      | EGP<br>10B | EGP<br>10C | EGP<br>10D | EGP<br>10F | EGP<br>10G | UNITS |
|----------------------------------------------------------------------------------------------------------------|--------------------|-----------------|------------|------------|------------|------------|------------|-------|
| Maximum recurrent peak reverse voltage                                                                         | V <sub>RRM</sub>   | 50              | 100        | 150        | 200        | 300        | 400        | V     |
| Maximum RMS voltage                                                                                            | V <sub>RMS</sub>   | 35              | 70         | 105        | 140        | 210        | 280        | V     |
| Maximum DC blocking voltage                                                                                    | V <sub>DC</sub>    | 50              | 100        | 150        | 200        | 300        | 400        | V     |
| Maximum average forward rectified current<br>9.5mm lead length @T <sub>A</sub> =75°C                           | I <sub>F(AV)</sub> | 1.0             |            |            |            |            |            | A     |
| Peak forward surge current<br>8.3ms single half-sine-wave<br>superimposed on rated load @T <sub>J</sub> =125°C | I <sub>FSM</sub>   | 30.0            |            |            |            |            |            | A     |
| Maximum instantaneous forward voltage<br>@ 1.0 A                                                               | V <sub>F</sub>     | 0.95            |            |            |            | 1.25       |            | V     |
| Maximum reverse current @T <sub>A</sub> =25°C<br>at rated DC blocking voltage @T <sub>A</sub> =125°C           | I <sub>R</sub>     | 5.0<br>100.0    |            |            |            |            |            | μ A   |
| Maximum reverse recovery time (Note1)                                                                          | t <sub>rr</sub>    | 50              |            |            |            |            |            | ns    |
| Typical junction capacitance (Note2)                                                                           | C <sub>J</sub>     | 22              |            |            |            | 15         |            | pF    |
| Typical thermal resistance (Note3)                                                                             | R <sub>θJA</sub>   | 50              |            |            |            |            |            | °C /W |
| Operating junction temperature range                                                                           | T <sub>J</sub>     | - 55 ---- + 150 |            |            |            |            |            | °C    |
| Storage temperature range                                                                                      | T <sub>STG</sub>   | - 55 ---- + 150 |            |            |            |            |            | °C    |

NOTE: 1. Measured with  $I_F=0.5\text{A}$ ,  $I_R=1\text{A}$ ,  $t_r=0.25\text{A}$ .

2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

3. Thermal resistance from junction to ambient.

FIG.1 –TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC



NOTES:1.RISE TIME=7ns MAX.INPUT IMPEDANCE=1MΩ.22pF  
2.RISE TIME=10ns MAX.SOURCE IMPEDANCE=50Ω

SET TIME BASE FOR 20/30 ns/cm

FIG.3 –TYPICAL FORWARD CHARACTERISTICS

INSTANTANEOUS FORWARD CURRENT  
AMPERES





FIG.4-TYPICAL REVERSE CHARACTERISTICS

PEAK FORWARD SURGE CURRENT  
AMPERES



NUMBER OF CYCLES AT 60Hz

FIG.5-TYPICAL JUNCTION CAPACITANCE

JUNCTION CAPACITANCE,pF




FIG.6-FORWARD DERATING CURVE

AVERAGE FORWARD CURRENT  
AMPERES

