


NOTES:

1. SEE SHEET 2 FOR PRODUCT DESCRIPTIONS AND TECHNICAL SPECIFICATIONS.
2. SEE CURRENT CATALOG FOR PATCH CORD LENGTHS AND PACKAGE QUANTITY.
3. FOR LENGTHS OTHER THAN THOSE LISTED IN CATALOG, CONTACT YOUR PANDUIT SALES PERSON.
4. TESTED TO EIA/TIA 568-B.3.
5. PATCH CORD ROUTING CONFIGURATION A TO B.
6. ALL MATERIALS AND COMPONENTS USED MEET THE MATERIAL RESTRICTIONS OF RoHS, (EUROPEAN DIRECTIVE 2002/95/EC ON THE RESTRICTION OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE RoHS TECHNICAL ADAPTATION COMMITTEE.

										SIMPLEX FIBER OPTIC PATCH CORD ST TO ST CONFIGURATION CUSTOMER DRAWING			
											PANDUIT TM CORP. TINLEY PARK, ILL 60477		
											ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: $(.X) (.XXX) \pm .010 (.031)$ $(.XX) (.031) \pm .03 (.08)$	DRAWING FILENAME MO2779CF_DC_00A.prt	
										DRAWN BY MC	SCALE NONE		
										REVIEW DRAWING NUMBERS SEE TABLE, SHT. 2	PART NO. 02779-36 DRAWING NO. 02779-36 (SHT. 1 of 21)	SIZE A	
R	06-04-07	MC		RELEASED TO PRODUCTION	02779-36					DATE 05-23-07			
REV	DATE	BY	CHK	DESCRIPTION	ECN - R	CUST	SUP	OTH	CHK'D				

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[F6S2-2M1Y](#) [F6S2-2M2Y](#) [F9S2-2M5Y](#)