

154-00016

# HellermannTyton

Article Number: 154-00016



Description: Flat Ribbon Adhesive Clamp, 2.2" Max Cable Width, 0.156" Hole Dia., PA66, Gray, 500/pkg

Base Data	
Local Order Number	FC2.2AH4
Type	FC2.2A
Color	Gray (GY)
Features and Benefits	<ul style="list-style-type: none"> <li>Adjustable height feature allows the clamp to close to the exact height of the ribbon cable.</li> <li>Releasable for easy access to cables when necessary.</li> <li>Available in adhesive or screw mount versions.</li> </ul>
Quantity Per	bag
Product Description	HellermannTyton's flat ribbon clamps route, protect and secure flat ribbon cables without damage to sensitive wires and cables. The unique, adjustable height feature allows the clamp to close to the exact height of the ribbon cable, using only as much force as needed to secure the cable. The releasable feature allows simple opening when access to the cable is necessary. These clamps are available in adhesive or screw mount versions.
Short Description	Flat Ribbon Adhesive Clamp, 2.2" Max Cable Width, 0.156" Hole Dia., PA66, Gray, 500/pkg
Product Dimensions	
Length L (Imperial)	0.75"
Length L (Metric)	19.0mm
Width W (Imperial)	2.6"
Width W (Metric)	66.0mm
Height H (Imperial)	0.5"
Height H (Metric)	12.7mm
Mounting Hole Diameter D (Imperial)	0.156"
Mounting Hole Diameter D (Metric)	4.0 mm
For Cable Width Max. (Metric)	55.9mm
For Cable Width Max. (Imperial)	2.2"
Mounting Hole Diameter D Max. (Metric)	4.0mm
Mounting Hole Diameter D Min. (Metric)	4.0mm

154-00016

**HellermannTyton**

Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Adhesive	Acrylate with base of polyurethane foam
	Adhesive Operating Temperature	to +230°F (+110°C)
	Flammability	UL94 V2 (excluding adhesive)
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Logistic and Packaging	ROHS Compliant	Yes
	Package Quantity (Metric)	500Pieces
	Customs Number(Schedule B)	3926909987